

Package ‘DatabaseConnector’

December 11, 2023

Type Package

Title Connecting to Various Database Platforms

Version 6.3.2

Date 2023-12-11

Description An R 'DataBase Interface' ('DBI') compatible interface to various database platforms ('PostgreSQL', 'Oracle', 'Microsoft SQL Server', 'Amazon Redshift', 'Microsoft Parallel Database Warehouse', 'IBM Netezza', 'Apache Impala', 'Google BigQuery', 'Snowflake', 'Spark', and 'SQLite'). Also includes support for fetching data as 'Andromeda' objects. Uses either 'Java Database Connectivity' ('JDBC') or other 'DBI' drivers to connect to databases.

SystemRequirements Java (>= 8)

Depends R (>= 4.0.0)

Imports rJava,

 SqlRender (>= 1.16.0),
 methods,
 stringr,
 readr,
 rlang,
 utils,
 DBI (>= 1.0.0),
 urlobjects,
 bit64,
 checkmate,
 digest,
 dbplyr (>= 2.2.0)

Suggests aws.s3,

 R.utils,
 withr,
 testthat,
 DBItest,
 knitr,
 rmarkdown,
 RSQlite,
 ssh,
 Andromeda,
 dplyr,
 RPostgres,
 odbc,

duckdb,
pool,
ParallelLogger

License Apache License

VignetteBuilder knitr

URL <https://ohdsi.github.io/DatabaseConnector/>, <https://github.com/OHDSI/DatabaseConnector>

BugReports <https://github.com/OHDSI/DatabaseConnector/issues>

Copyright See file COPYRIGHTS

RoxygenNote 7.2.3

Roxygen list(markdown = TRUE)

Encoding UTF-8

R topics documented:

assertTempEmulationSchemaSet	3
computeDataHash	4
connect	5
createConnectionDetails	9
createDbiConnectionDetails	12
createZipFile	13
DatabaseConnectorDriver	14
dateAdd	14
dateDiff	15
dateFromParts	15
day	16
dbAppendTable,DatabaseConnectorConnection,character-method	16
dbClearResult,DatabaseConnectorDbiResult-method	18
dbClearResult,DatabaseConnectorJdbcResult-method	18
dbColumnInfo,DatabaseConnectorDbiResult-method	19
dbColumnInfo,DatabaseConnectorJdbcResult-method	20
dbConnect,DatabaseConnectorDriver-method	20
dbCreateTable,DatabaseConnectorConnection-method	21
dbDisconnect,DatabaseConnectorConnection-method	23
dbExecute,DatabaseConnectorConnection,character-method	23
dbExistsTable,DatabaseConnectorConnection,character-method	24
dbFetch,DatabaseConnectorDbiResult-method	25
dbFetch,DatabaseConnectorJdbcResult-method	26
dbGetInfo,DatabaseConnectorConnection-method	27
dbGetInfo,DatabaseConnectorDriver-method	28
dbGetQuery,DatabaseConnectorConnection,character-method	29
dbGetRowCount,DatabaseConnectorDbiResult-method	30
dbGetRowCount,DatabaseConnectorJdbcResult-method	31
dbGetRowsAffected,DatabaseConnectorDbiResult-method	32
dbGetRowsAffected,DatabaseConnectorJdbcResult-method	32
dbGetStatement,DatabaseConnectorDbiResult-method	33
dbGetStatement,DatabaseConnectorJdbcResult-method	34
dbHasCompleted,DatabaseConnectorDbiResult-method	34

dbHasCompleted,DatabaseConnectorJdbcResult-method	35
dbIsValid,DatabaseConnectorDbiConnection-method	36
dbIsValid,DatabaseConnectorJdbcConnection-method	37
dbListFields,DatabaseConnectorConnection,character-method	38
dbListTables,DatabaseConnectorConnection-method	39
dbms	40
dbReadTable,DatabaseConnectorConnection,character-method	40
dbRemoveTable,DatabaseConnectorConnection,ANY-method	42
dbSendQuery,DatabaseConnectorDbiConnection,character-method	43
dbSendQuery,DatabaseConnectorJdbcConnection,character-method	44
dbSendStatement,DatabaseConnectorConnection,character-method	45
dbUnloadDriver,DatabaseConnectorDriver-method	46
dbWriteTable,DatabaseConnectorConnection,ANY-method	47
disconnect	48
downloadJdbcDrivers	49
dropEmulatedTempTables	50
eoMonth	51
executeSql	51
existsTable	52
extractQueryTimes	53
getAvailableJavaHeapSpace	54
getTableNames	54
inDatabaseSchema	55
insertTable	56
isSqlReservedWord	58
jdbcDrivers	58
lowLevelExecuteSql	59
lowLevelQuerySql	59
lowLevelQuerySqlToAndromeda	60
month	61
querySql	62
querySqlToAndromeda	63
renderTranslateExecuteSql	64
renderTranslateQueryApplyBatched	66
renderTranslateQuerySql	68
renderTranslateQuerySqlToAndromeda	70
requiresTempEmulation	71
year	72

assertTempEmulationSchemaSet

Assert the temp emulation schema is set

Description

Asserts the temp emulation schema is set for DBMSs requiring temp table emulation.

If you know your code uses temp tables, it is a good idea to call this function first, so it can throw an informative error if the user forgot to set the temp emulation schema.

Usage

```
assertTempEmulationSchemaSet(
    dbms,
    tempEmulationSchema = getOption("sqlRenderTempEmulationSchema")
)
```

Arguments

<code>dbms</code>	The type of DBMS running on the server. See connect() or createConnectionDetails() for valid values.
<code>tempEmulationSchema</code>	The temp emulation schema specified by the user.

Value

Does not return anything. Throws an error if the DBMS requires temp emulation but the temp emulation schema is not set.

<code>computeDataHash</code>	<i>Compute hash of data</i>
------------------------------	-----------------------------

Description

Compute a hash of the data in the database schema. If the data changes, this should produce a different hash code. Specifically, the hash is based on the field names, field types, and table row counts.

Usage

```
computeDataHash(connection, databaseSchema, tables = NULL, progressBar = TRUE)
```

Arguments

<code>connection</code>	The connection to the database server created using either connect() or dbConnect() .
<code>databaseSchema</code>	The name of the database schema. See details for platform-specific details.
<code>tables</code>	(Optional) A list of tables to restrict to.
<code>progressBar</code>	When true, a progress bar is shown based on the number of tables in the database schema.

Details

The `databaseSchema` argument is interpreted differently according to the different platforms: SQL Server and PDW: The `databaseSchema` schema should specify both the database and the schema, e.g. '`my_database.dbo`'. Impala: the `databaseSchema` should specify the database. Oracle: The `databaseSchema` should specify the Oracle '`user`'. All other : The `databaseSchema` should specify the schema.

Value

A string representing the MD5 hash code.

connect

connect

Description

Creates a connection to a database server .There are four ways to call this function:

- `connect(dbms, user, password, server, port, extraSettings, oracleDriver, pathToDriver)`
- `connect(connectionDetails)`
- `connect(dbms, connectionString, pathToDriver))`
- `connect(dbms, connectionString, user, password, pathToDriver)`

DBMS parameter details::

Depending on the DBMS, the function arguments have slightly different interpretations:

Oracle:

- `user`. The user name used to access the server
- `password`. The password for that user
- `server`. This field contains the SID, or host and servicename, SID, or TNSName: 'sid', 'host/sid', 'host/service name', or 'tnsname'
- `port`. Specifies the port on the server (default = 1521)
- `extraSettings`. The configuration settings for the connection (i.e. SSL Settings such as "(PROTOCOL=tcpS)")
- `oracleDriver`. The driver to be used. Choose between "thin" or "oci".
- `pathToDriver`. The path to the folder containing the Oracle JDBC driver JAR files.

Microsoft SQL Server:

- `user`. The user used to log in to the server. If the user is not specified, Windows Integrated Security will be used, which requires the SQL Server JDBC drivers to be installed (see details below).
- `password`. The password used to log on to the server
- `server`. This field contains the host name of the server
- `port`. Not used for SQL Server
- `extraSettings`. The configuration settings for the connection (i.e. SSL Settings such as "encrypt=true; trustServerCertificate=false;")
- `pathToDriver`. The path to the folder containing the SQL Server JDBC driver JAR files.

Microsoft PDW:

- `user`. The user used to log in to the server. If the user is not specified, Windows Integrated Security will be used, which requires the SQL Server JDBC drivers to be installed (see details below).
- `password`. The password used to log on to the server
- `server`. This field contains the host name of the server
- `port`. Not used for SQL Server
- `extraSettings`. The configuration settings for the connection (i.e. SSL Settings such as "encrypt=true; trustServerCertificate=false;")
- `pathToDriver`. The path to the folder containing the SQL Server JDBC driver JAR files.

PostgreSQL:

- **user.** The user used to log in to the server
- **password.** The password used to log on to the server
- **server.** This field contains the host name of the server and the database holding the relevant schemas: host/database
- **port.** Specifies the port on the server (default = 5432)
- **extraSettings.** The configuration settings for the connection (i.e. SSL Settings such as "ssl=true")
- **pathToDriver.** The path to the folder containing the PostgreSQL JDBC driver JAR files.

Redshift:

- **user.** The user used to log in to the server
- **password.** The password used to log on to the server
- **server.** This field contains the host name of the server and the database holding the relevant schemas: host/database
- **port.** Specifies the port on the server (default = 5439)
- **'extraSettings** The configuration settings for the connection (i.e. SSL Settings such as "ssl=true&sslfactory=com.amazonaws.jdbc.ssl.AmazonSSLFactory")
- **pathToDriver.** The path to the folder containing the RedShift JDBC driver JAR files.

Netezza:

- **user.** The user used to log in to the server
- **password.** The password used to log on to the server
- **server.** This field contains the host name of the server and the database holding the relevant schemas: host/database
- **port.** Specifies the port on the server (default = 5480)
- **extraSettings.** The configuration settings for the connection (i.e. SSL Settings such as "ssl=true")
- **pathToDriver.** The path to the folder containing the Netezza JDBC driver JAR file (nzjdbc.jar).

Impala:

- **user.** The user name used to access the server
- **password.** The password for that user
- **server.** The host name of the server
- **port.** Specifies the port on the server (default = 21050)
- **extraSettings.** The configuration settings for the connection (i.e. SSL Settings such as "SSLKeyStorePwd=*****")
- **pathToDriver.** The path to the folder containing the Impala JDBC driver JAR files.

SQLite:

- **server.** The path to the SQLite file.

Spark / Databricks:

Currently both JDBC and ODBC connections are supported for Spark. Set the `connectionString` argument to use JDBC, otherwise ODBC is used:

- **connectionString.** The JDBC connection string (e.g. something like 'jdbc:databricks://my-org.cloud.databricks.com:443/default;transportMode=http;ssl=1;AuthMech=3;httpPath=/sql/1.0/warehouses/abc')
- **user.** The user name used to access the server. This can be set to 'token' when using a personal token (recommended).
- **password.** The password for that user. This should be your personal token when using a personal token (recommended).
- **server.** The host name of the server (when using ODBC), e.g. 'my-org.cloud.databricks.com')

- `port`. Specifies the port on the server (when using ODBC)
- `extraSettings`. Additional settings for the ODBC connection, for example `extraSettings = list(HTTPPath = "/sql/1.0/warehouses/abcde12345", SSL = 1, ThriftTransport = 2, AuthMech = 3)`

Snowflake:

- `connectionString`. The connection string (e.g. starting with 'jdbc:snowflake://host:port/?db=database').
- `user`. The user name used to access the server.
- `password`. The password for that user.

Windows authentication for SQL Server::

To be able to use Windows authentication for SQL Server (and PDW), you have to install the JDBC driver. Download the version 9.2.0 .zip from [Microsoft](#) and extract its contents to a folder. In the extracted folder you will find the file `sqljdbc_9.2/enu/auth/x64/mssql-jdbc_auth-9.2.0.x64.dll` (64-bits) or `sqljdbc_9.2/enu/auth/x86/mssql-jdbc_auth-9.2.0.x86.dll` (32-bits), which needs to be moved to location on the system path, for example to `c:/windows/system32`. If you not have write access to any folder in the system path, you can also specify the path to the folder containing the dll by setting the environmental variable `PATH_TO_AUTH_DLL`, so for example `Sys.setenv("PATH_TO_AUTH_DLL" = "c:/temp")` Note that the environmental variable needs to be set before calling `connect()` for the first time.

Arguments

<code>connectionDetails</code>	An object of class <code>connectionDetails</code> as created by the createConnectionDetails() function.
<code>dbms</code>	The type of DBMS running on the server. Valid values are <ul style="list-style-type: none"> • "oracle" for Oracle • "postgresql" for PostgreSQL • "redshift" for Amazon Redshift • "sql server" for Microsoft SQL Server • "pdw" for Microsoft Parallel Data Warehouse (PDW) • "netezza" for IBM Netezza • "bigquery" for Google BigQuery • "sqlite" for SQLite • "sqlite extended" for SQLite with extended types (DATE and DATETIME) • "spark" for Spark • "snowflake" for Snowflake
<code>user</code>	The user name used to access the server.
<code>password</code>	The password for that user.
<code>server</code>	The name of the server.
<code>port</code>	(optional) The port on the server to connect to.
<code>extraSettings</code>	(optional) Additional configuration settings specific to the database provider to configure things as security for SSL. For connections using JDBC these will be appended to end of the connection string. For connections using DBI, these settings will additionally be used to call dbConnect() .
<code>oracleDriver</code>	Specify which Oracle drive you want to use. Choose between "thin" or "oci".

<code>connectionString</code>	The JDBC connection string. If specified, the <code>server</code> , <code>port</code> , <code>extraSettings</code> , and <code>oracleDriver</code> fields are ignored. If <code>user</code> and <code>password</code> are not specified, they are assumed to already be included in the connection string.
<code>pathToDriver</code>	Path to a folder containing the JDBC driver JAR files. See downloadJdbcDrivers() for instructions on how to download the relevant drivers.

Details

This function creates a connection to a database.

Value

An object that extends `DBIConnection` in a database-specific manner. This object is used to direct commands to the database engine.

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost/postgres",
  user = "root",
  password = "xxx"
)
conn <- connect(connectionDetails)
dbGetQuery(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

conn <- connect(dbms = "sql server", server = "RNDUSRDHIT06.jnj.com")
dbGetQuery(conn, "SELECT COUNT(*) FROM concept")
disconnect(conn)

conn <- connect(
  dbms = "oracle",
  server = "127.0.0.1/xe",
  user = "system",
  password = "xxx",
  pathToDriver = "c:/temp"
)
dbGetQuery(conn, "SELECT COUNT(*) FROM test_table")
disconnect(conn)

conn <- connect(
  dbms = "postgresql",
  connectionString = "jdbc:postgresql://127.0.0.1:5432/cmd_database"
)
dbGetQuery(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

## End(Not run)
```

```
createConnectionDetails
    createConnectionDetails
```

Description

Creates a list containing all details needed to connect to a database. There are three ways to call this function:

- `createConnectionDetails(dbms, user, password, server, port, extraSettings, oracleDriver, pathToDriver)`
- `createConnectionDetails(dbms, connectionString, pathToDriver)`
- `createConnectionDetails(dbms, connectionString, user, password, pathToDriver)`

DBMS parameter details::

Depending on the DBMS, the function arguments have slightly different interpretations:

Oracle:

- `user`. The user name used to access the server
- `password`. The password for that user
- `server`. This field contains the SID, or host and servicename, SID, or TNSName: '`'sid'`', '`'host/sid'`', '`'host/service name'`', or '`'tnsname'`'
- `port`. Specifies the port on the server (default = 1521)
- `extraSettings`. The configuration settings for the connection (i.e. SSL Settings such as "`(PROTOCOL=tcpS)`")
- `oracleDriver`. The driver to be used. Choose between "thin" or "oci".
- `pathToDriver`. The path to the folder containing the Oracle JDBC driver JAR files.

Microsoft SQL Server:

- `user`. The user used to log in to the server. If the user is not specified, Windows Integrated Security will be used, which requires the SQL Server JDBC drivers to be installed (see details below).
- `password`. The password used to log on to the server
- `server`. This field contains the host name of the server
- `port`. Not used for SQL Server
- `extraSettings`. The configuration settings for the connection (i.e. SSL Settings such as "`"encrypt=true; trustServerCertificate=false;"`")
- `pathToDriver`. The path to the folder containing the SQL Server JDBC driver JAR files.

Microsoft PDW:

- `user`. The user used to log in to the server. If the user is not specified, Windows Integrated Security will be used, which requires the SQL Server JDBC drivers to be installed (see details below).
- `password`. The password used to log on to the server
- `server`. This field contains the host name of the server
- `port`. Not used for SQL Server
- `extraSettings`. The configuration settings for the connection (i.e. SSL Settings such as "`"encrypt=true; trustServerCertificate=false;"`")
- `pathToDriver`. The path to the folder containing the SQL Server JDBC driver JAR files.

PostgreSQL:

- **user.** The user used to log in to the server
- **password.** The password used to log on to the server
- **server.** This field contains the host name of the server and the database holding the relevant schemas: host/database
- **port.** Specifies the port on the server (default = 5432)
- **extraSettings.** The configuration settings for the connection (i.e. SSL Settings such as "ssl=true")
- **pathToDriver.** The path to the folder containing the PostgreSQL JDBC driver JAR files.

Redshift:

- **user.** The user used to log in to the server
- **password.** The password used to log on to the server
- **server.** This field contains the host name of the server and the database holding the relevant schemas: host/database
- **port.** Specifies the port on the server (default = 5439)
- **'extraSettings** The configuration settings for the connection (i.e. SSL Settings such as "ssl=true&sslfactory=com.amazonaws.redshift.jdbc.sslfactory.SSLConnectionFactory")
- **pathToDriver.** The path to the folder containing the RedShift JDBC driver JAR files.

Netezza:

- **user.** The user used to log in to the server
- **password.** The password used to log on to the server
- **server.** This field contains the host name of the server and the database holding the relevant schemas: host/database
- **port.** Specifies the port on the server (default = 5480)
- **extraSettings.** The configuration settings for the connection (i.e. SSL Settings such as "ssl=true")
- **pathToDriver.** The path to the folder containing the Netezza JDBC driver JAR file (nzjdbc.jar).

Impala:

- **user.** The user name used to access the server
- **password.** The password for that user
- **server.** The host name of the server
- **port.** Specifies the port on the server (default = 21050)
- **extraSettings.** The configuration settings for the connection (i.e. SSL Settings such as "SSLKeyStorePwd=*****")
- **pathToDriver.** The path to the folder containing the Impala JDBC driver JAR files.

SQLite:

- **server.** The path to the SQLite file.

Spark / Databricks:

Currently both JDBC and ODBC connections are supported for Spark. Set the `connectionString` argument to use JDBC, otherwise ODBC is used:

- **connectionString.** The JDBC connection string (e.g. something like 'jdbc:databricks://my-org.cloud.databricks.com:443/default;transportMode=http;ssl=1;AuthMech=3;httpPath=/sql/1.0/warehouses/abc')
- **user.** The user name used to access the server. This can be set to 'token' when using a personal token (recommended).
- **password.** The password for that user. This should be your personal token when using a personal token (recommended).

- `server`. The host name of the server (when using ODBC), e.g. 'my-org.cloud.databricks.com')
- `port`. Specifies the port on the server (when using ODBC)
- `extraSettings`. Additional settings for the ODBC connection, for example `extraSettings = list(HTTPPath = "/sql/1.0/warehouses/abcde12345", SSL = 1, ThriftTransport = 2, AuthMech = 3)`

Snowflake:

- `connectionString`. The connection string (e.g. starting with 'jdbc:snowflake://host:port/?db=database').
- `user`. The user name used to access the server.
- `password`. The password for that user.

Windows authentication for SQL Server::

To be able to use Windows authentication for SQL Server (and PDW), you have to install the JDBC driver. Download the version 9.2.0 .zip from [Microsoft](#) and extract its contents to a folder. In the extracted folder you will find the file `sqljdbc_9.2/enu/auth/x64/mssql-jdbc_auth-9.2.0.x64.dll` (64-bits) or `sqljdbc_9.2/enu/auth/x86/mssql-jdbc_auth-9.2.0.x86.dll` (32-bits), which needs to be moved to location on the system path, for example to `c:/windows/system32`. If you not have write access to any folder in the system path, you can also specify the path to the folder containing the dll by setting the environmental variable `PATH_TO_AUTH_DLL`, so for example `Sys.setenv("PATH_TO_AUTH_DLL" = "c:/temp")` Note that the environmental variable needs to be set before calling `connect()` for the first time.

Arguments

<code>dbms</code>	The type of DBMS running on the server. Valid values are <ul style="list-style-type: none"> • "oracle" for Oracle • "postgresql" for PostgreSQL • "redshift" for Amazon Redshift • "sql server" for Microsoft SQL Server • "pdw" for Microsoft Parallel Data Warehouse (PDW) • "netezza" for IBM Netezza • "bigquery" for Google BigQuery • "sqlite" for SQLite • "sqlite extended" for SQLite with extended types (DATE and DATETIME) • "spark" for Spark • "snowflake" for Snowflake
<code>user</code>	The user name used to access the server.
<code>password</code>	The password for that user.
<code>server</code>	The name of the server.
<code>port</code>	(optional) The port on the server to connect to.
<code>extraSettings</code>	(optional) Additional configuration settings specific to the database provider to configure things as security for SSL. For connections using JDBC these will be appended to end of the connection string. For connections using DBI, these settings will additionally be used to call <code>dbConnect()</code> .
<code>oracleDriver</code>	Specify which Oracle drive you want to use. Choose between "thin" or "oci".
<code>connectionString</code>	The JDBC connection string. If specified, the <code>server</code> , <code>port</code> , <code>extraSettings</code> , and <code>oracleDriver</code> fields are ignored. If <code>user</code> and <code>password</code> are not specified, they are assumed to already be included in the connection string.
<code>pathToDriver</code>	Path to a folder containing the JDBC driver JAR files. See downloadJdbcDrivers() for instructions on how to download the relevant drivers.

Details

This function creates a list containing all details needed to connect to a database. The list can then be used in the [connect\(\)](#) function.

It is highly recommended to use a secure approach to storing credentials, so not to have your credentials in plain text in your R scripts. The examples demonstrate how to use the [keyring](#) package.

Value

A list with all the details needed to connect to a database.

Examples

```
## Not run:
# Needs to be done only once on a machine. Credentials will then be stored in
# the operating system's secure credential manager:
keyring::key_set_with_value("server", password = "localhost/postgres")
keyring::key_set_with_value("user", password = "root")
keyring::key_set_with_value("password", password = "secret")

# Create connection details using keyring. Note: the connection details will
# not store the credentials themselves, but the reference to get the credentials.
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = keyring::key_get("server"),
  user = keyring::key_get("user"),
  password = keyring::key_get("password"),
)
conn <- connect(connectionDetails)
dbGetQuery(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

## End(Not run)
```

createDbiConnectionDetails

Create DBI connection details

Description

For advanced users only. This function will allow [DatabaseConnector](#) to wrap any DBI driver. Using a driver that [DatabaseConnector](#) hasn't been tested with may give unpredictable performance. Use at your own risk. No support will be provided.

Usage

```
createDbiConnectionDetails(dbms, drv, ...)
```

Arguments

dbms	The type of DBMS running on the server. Valid values are <ul style="list-style-type: none"> • "oracle" for Oracle • "postgresql" for PostgreSQL
------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------

	<ul style="list-style-type: none"> • "redshift" for Amazon Redshift • "sql server" for Microsoft SQL Server • "pdw" for Microsoft Parallel Data Warehouse (PDW) • "netezza" for IBM Netezza • "bigquery" for Google BigQuery • "sqlite" for SQLite • "sqlite extended" for SQLite with extended types (DATE and DATETIME) • "spark" for Spark • "snowflake" for Snowflake
drv	An object that inherits from DBIDriver, or an existing DBIConnection object (in order to clone an existing connection).
...	authentication arguments needed by the DBMS instance; these typically include user, password, host, port, dbname, etc. For details see the appropriate DBIDriver

Value

A list with all the details needed to connect to a database.

createZipFile

Compress files and/or folders into a single zip file

Description

Compress files and/or folders into a single zip file

Usage

```
createZipFile(zipFile, files, rootFolder = getwd(), compressionLevel = 9)
```

Arguments

zipFile	The path to the zip file to be created.
files	The files and/or folders to be included in the zip file. Folders will be included recursively.
rootFolder	The root folder. All files will be stored with relative paths relative to this folder.
compressionLevel	A number between 1 and 9. 9 compresses best, but it also takes the longest.

Details

Uses Java's compression library to create a zip file. It is similar to `utils::zip`, except that it does not require an external zip tool to be available on the system path.

DatabaseConnectorDriver

Create a DatabaseConnectorDriver object

Description

Create a DatabaseConnectorDriver object

Usage

```
DatabaseConnectorDriver()
```

dateAdd

Add an interval to a date

Description

This function is provided primarily to be used together with `dbplyr` when querying a database. It will also work in `dplyr` against data frames.

Usage

```
dateAdd(interval, number, date)
```

Arguments

- | | |
|----------|---------------------------------------------------------------|
| interval | Unit for the interval. Can be "day", "week", "month", "year". |
| number | The number of units to add to the date. |
| date | The date to add to. |

Value

A new date.

Examples

```
dateAdd("day", 10, as.Date("2000-01-01"))
```

dateDiff	<i>Compute difference between dates</i>
----------	-----------------------------------------

Description

This function is provided primarily to be used together with `dbplyr` when querying a database. It will also work in `dplyr` against data frames.

Usage

```
dateDiff(interval, date1, date2)
```

Arguments

interval	Unit for the interval. Can be "day", "week", "month", "year".
date1	The first date.
date2	The second date.

Value

The numeric value of the difference.

Examples

```
dateDiff("day", as.Date("2000-01-01"), as.Date("2000-03-01"))
```

dateFromParts	<i>Construct a date from parts</i>
---------------	------------------------------------

Description

This function is provided primarily to be used together with `dbplyr` when querying a database. It will also work in `dplyr` against data frames.

Usage

```
dateFromParts(year, month, day)
```

Arguments

year	The calendar year.
month	The calendar month (1 = January).
day	The day of the month.

Value

The date.

Examples

```
dateFromParts(2000, 1, 5)
```

day	<i>Extract the day from a date</i>
-----	------------------------------------

Description

This function is provided primarily to be used together with `dbplyr` when querying a database. It will also work in `dplyr` against data frames.

Usage

```
day(date)
```

Arguments

date	The date.
------	-----------

Value

The day

Examples

```
day(as.Date("2000-02-01"))
```

<code>dbAppendTable,DatabaseConnectorConnection,character-method</code>	
-------------------------------------------------------------------------	--

Insert rows into a table

Description

The `dbAppendTable()` method assumes that the table has been created beforehand, e.g. with `dbCreateTable()`. The default implementation calls `sqlAppendTableTemplate()` and then `dbExecute()` with the `param` argument. Backends compliant to ANSI SQL 99 which use `?` as a placeholder for prepared queries don't need to override it. Backends with a different SQL syntax which use `?` as a placeholder for prepared queries can override `sqlAppendTable()`. Other backends (with different placeholders or with entirely different ways to create tables) need to override the `dbAppendTable()` method.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbAppendTable(
  conn,
  name,
  value,
  databaseSchema = NULL,
  temporary = FALSE,
  oracleTempSchema = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  ...,
  row.names = NULL
)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. <code>Id(schema = "my_schema", table = "table_name")</code> • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. <code>SQL(''my_schema''. "table_name"')</code>
value	A data frame of values. The column names must be consistent with those in the target table in the database.
databaseSchema	The name of the database schema. See details for platform-specific details.
temporary	Should the table created as a temp table?
oracleTempSchema	<small>DEPRECATED: use tempEmulationSchema instead.</small>
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
...	Other parameters passed on to methods.
row.names	Must be NULL.

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the databaseSchema should specify the database. Oracle: The databaseSchema should specify the Oracle 'user'. All other : The databaseSchema should specify the schema.

Value

`dbAppendTable()` returns a scalar numeric.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

dbClearResult,DatabaseConnectorDbiResult-method

Clear a result set

Description

Frees all resources (local and remote) associated with a result set. This step is mandatory for all objects obtained by calling [dbSendQuery\(\)](#) or [dbSendStatement\(\)](#).

Usage

```
## S4 method for signature 'DatabaseConnectorDbiResult'
dbClearResult(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

`dbClearResult()` returns TRUE, invisibly, for result sets obtained from both `dbSendQuery()` and `dbSendStatement()`.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbClearResult,DatabaseConnectorJdbcResult-method

Clear a result set

Description

Frees all resources (local and remote) associated with a result set. This step is mandatory for all objects obtained by calling [dbSendQuery\(\)](#) or [dbSendStatement\(\)](#).

Usage

```
## S4 method for signature 'DatabaseConnectorJdbcResult'
dbClearResult(res, ...)
```

Arguments

- res An object inheriting from [DBIResult](#).
 ... Other arguments passed on to methods.

Value

`dbClearResult()` returns TRUE, invisibly, for result sets obtained from both `dbSendQuery()` and `dbSendStatement()`.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbColumnInfo,DatabaseConnectorDbiResult-method

Information about result types

Description

Produces a data.frame that describes the output of a query. The data.frame should have as many rows as there are output fields in the result set, and each column in the data.frame describes an aspect of the result set field (field name, type, etc.)

Usage

```
## S4 method for signature 'DatabaseConnectorDbiResult'
dbColumnInfo(res, ...)
```

Arguments

- res An object inheriting from [DBIResult](#).
 ... Other arguments passed on to methods.

Value

`dbColumnInfo()` returns a data frame with at least two columns "name" and "type" (in that order) (and optional columns that start with a dot). The "name" and "type" columns contain the names and types of the R columns of the data frame that is returned from [dbFetch\(\)](#). The "type" column is of type character and only for information. Do not compute on the "type" column, instead use `dbFetch(res, n = 0)` to create a zero-row data frame initialized with the correct data types.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbColumnInfo,DatabaseConnectorJdbcResult-method*Information about result types***Description**

Produces a data.frame that describes the output of a query. The data.frame should have as many rows as there are output fields in the result set, and each column in the data.frame describes an aspect of the result set field (field name, type, etc.)

Usage

```
## S4 method for signature 'DatabaseConnectorJdbcResult'
dbColumnInfo(res, ...)
```

Arguments

- | | |
|-----|-------------------------------------------------------|
| res | An object inheriting from DBIResult . |
| ... | Other arguments passed on to methods. |

Value

`dbColumnInfo()` returns a data frame with at least two columns "name" and "type" (in that order) (and optional columns that start with a dot). The "name" and "type" columns contain the names and types of the R columns of the data frame that is returned from [dbFetch\(\)](#). The "type" column is of type character and only for information. Do not compute on the "type" column, instead use `dbFetch(res, n = 0)` to create a zero-row data frame initialized with the correct data types.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbConnect,DatabaseConnectorDriver-method*Create a connection to a DBMS***Description**

Connect to a database. This function is synonymous with the [connect\(\)](#) function. except a dummy driver needs to be specified

Usage

```
## S4 method for signature 'DatabaseConnectorDriver'
dbConnect(drv, ...)
```

Arguments

- drv The result of the [DatabaseConnectorDriver\(\)](#) function
 ... Other parameters. These are the same as expected by the [connect\(\)](#) function.

Value

Returns a DatabaseConnectorConnection object that can be used with most of the other functions in this package.

Examples

```
## Not run:
conn <- dbConnect(DatabaseConnectorDriver(),
  dbms = "postgresql",
  server = "localhost/ohdsi",
  user = "joe",
  password = "secret"
)
querySql(conn, "SELECT * FROM cdm_synpuf.person;")
dbDisconnect(conn)

## End(Not run)
```

dbCreateTable,DatabaseConnectorConnection-method

Create a table in the database

Description

The default dbCreateTable() method calls [sqlCreateTable\(\)](#) and [dbExecute\(\)](#). Backends compliant to ANSI SQL 99 don't need to override it. Backends with a different SQL syntax can override [sqlCreateTable\(\)](#), backends with entirely different ways to create tables need to override this method.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection'
dbCreateTable(
  conn,
  name,
  fields,
  databaseSchema = NULL,
  oracleTempSchema = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  ...,
  row.names = NULL,
  temporary = FALSE
)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. <code>Id(schema = "my_schema", table = "table_name")</code> • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. <code>SQL(''my_schema''. "table_name"')</code>
fields	Either a character vector or a data frame. A named character vector: Names are column names, values are types. Names are escaped with dbQuoteIdentifier() . Field types are unescaped. A data frame: field types are generated using dbDataType() .
databaseSchema	The name of the database schema. See details for platform-specific details.
oracleTempSchema	DEPRECATED: use tempEmulationSchema instead.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
...	Other parameters passed on to methods.
row.names	Must be NULL.
temporary	Should the table created as a temp table?

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the databaseSchema should specify the database. Oracle: The databaseSchema should specify the Oracle 'user'. All other : The databaseSchema should specify the schema.

Value

`dbCreateTable()` returns TRUE, invisibly.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

dbDisconnect,DatabaseConnectorConnection-method
Disconnect (close) a connection

Description

This closes the connection, discards all pending work, and frees resources (e.g., memory, sockets).

Usage

```
## S4 method for signature 'DatabaseConnectorConnection'
dbDisconnect(conn)
```

Arguments

conn A [DBIConnection](#) object, as returned by [dbConnect\(\)](#).

Value

`dbDisconnect()` returns TRUE, invisibly.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

dbExecute,DatabaseConnectorConnection,character-method
Execute an update statement, query number of rows affected, and then close result set

Description

Executes a statement and returns the number of rows affected. `dbExecute()` comes with a default implementation (which should work with most backends) that calls [dbSendStatement\(\)](#), then [dbGetRowsAffected\(\)](#), ensuring that the result is always free'd by [dbClearResult\(\)](#). For passing query parameters, see [dbBind\(\)](#), in particular the "The command execution flow" section.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbExecute(conn, statement, translate = TRUE, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
statement	a character string containing SQL.
translate	Translate the query using SqlRender?
...	Other parameters passed on to methods.

Details

You can also use `dbExecute()` to call a stored procedure that performs data manipulation or other actions that do not return a result set. To execute a stored procedure that returns a result set, or a data manipulation query that also returns a result set such as `INSERT INTO ... RETURNING ...`, use `dbGetQuery()` instead.

Value

`dbExecute()` always returns a scalar numeric that specifies the number of rows affected by the statement.

See Also

For queries: `dbSendQuery()` and `dbGetQuery()`.

Other DBIConnection generics: `DBIConnection-class`, `dbAppendTable()`, `dbCreateTable()`, `dbDataType()`, `dbDisconnect()`, `dbExistsTable()`, `dbGetException()`, `dbGetInfo()`, `dbGetQuery()`, `dbIsReadOnly()`, `dbIsValid()`, `dbListFields()`, `dbListObjects()`, `dbListResults()`, `dbListTables()`, `dbReadTable()`, `dbRemoveTable()`, `dbSendQuery()`, `dbSendStatement()`, `dbWriteTable()`

`dbExistsTable,DatabaseConnectorConnection,character-method`

Does a table exist?

Description

Returns if a table given by name exists in the database.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbExistsTable(conn, name, databaseSchema = NULL, ...)
```

Arguments

conn	A <code>DBIConnection</code> object, as returned by <code>dbConnect()</code> .
name	The table name, passed on to <code>dbQuoteIdentifier()</code> . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to <code>Id()</code> with components to the fully qualified table name, e.g. <code>Id(schema = "my_schema", table = "table_name")</code> • a call to <code>SQL()</code> with the quoted and fully qualified table name given verbatim, e.g. <code>SQL(''my_schema''. "table_name"')</code>
databaseSchema	The name of the database schema. See details for platform-specific details.
...	Other parameters passed on to methods.

Details

The `databaseSchema` argument is interpreted differently according to the different platforms: SQL Server and PDW: The `databaseSchema` schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the `databaseSchema` should specify the database. Oracle: The `databaseSchema` should specify the Oracle 'user'. All other : The `databaseSchema` should specify the schema.

Value

`dbExistsTable()` returns a logical scalar, TRUE if the table or view specified by the name argument exists, FALSE otherwise.

This includes temporary tables if supported by the database.

See Also

Other DBIConnection generics: `DBIConnection-class`, `dbAppendTable()`, `dbCreateTable()`, `dbDataType()`, `dbDisconnect()`, `dbExecute()`, `dbGetException()`, `dbGetInfo()`, `dbGetQuery()`, `dbIsReadOnly()`, `dbIsValid()`, `dbListFields()`, `dbListObjects()`, `dbListResults()`, `dbListTables()`, `dbReadTable()`, `dbRemoveTable()`, `dbSendQuery()`, `dbSendStatement()`, `dbWriteTable()`

dbFetch,DatabaseConnectorDbiResult-method

Fetch records from a previously executed query

Description

Fetch the next n elements (rows) from the result set and return them as a data.frame.

Usage

```
## S4 method for signature 'DatabaseConnectorDbiResult'
dbFetch(res, n = -1, ...)
```

Arguments

<code>res</code>	An object inheriting from <code>DBIResult</code> , created by <code>dbSendQuery()</code> .
<code>n</code>	maximum number of records to retrieve per fetch. Use <code>n = -1</code> or <code>n = Inf</code> to retrieve all pending records. Some implementations may recognize other special values.
<code>...</code>	Other arguments passed on to methods.

Details

`fetch()` is provided for compatibility with older DBI clients - for all new code you are strongly encouraged to use `dbFetch()`. The default implementation for `dbFetch()` calls `fetch()` so that it is compatible with existing code. Modern backends should implement for `dbFetch()` only.

Value

`dbFetch()` always returns a `data.frame` with as many rows as records were fetched and as many columns as fields in the result set, even if the result is a single value or has one or zero rows.

See Also

Close the result set with `dbClearResult()` as soon as you finish retrieving the records you want.

Other DBIResult generics: `DBIResult-class`, `dbBind()`, `dbClearResult()`, `dbColumnInfo()`, `dbGetInfo()`, `dbGetRowCount()`, `dbGetRowsAffected()`, `dbGetStatement()`, `dbHasCompleted()`, `dbIsReadOnly()`, `dbIsValid()`, `dbQuoteIdentifier()`, `dbQuoteLiteral()`, `dbQuoteString()`, `dbUnquoteIdentifier()`

dbFetch,DatabaseConnectorJdbcResult-method

Fetch records from a previously executed query

Description

Fetch the next n elements (rows) from the result set and return them as a data.frame.

Usage

```
## S4 method for signature 'DatabaseConnectorJdbcResult'  
dbFetch(res, n = -1, ...)
```

Arguments

res	An object inheriting from DBIResult , created by dbSendQuery() .
n	maximum number of records to retrieve per fetch. Use n = -1 or n = Inf to retrieve all pending records. Some implementations may recognize other special values.
...	Other arguments passed on to methods.

Details

`fetch()` is provided for compatibility with older DBI clients - for all new code you are strongly encouraged to use `dbFetch()`. The default implementation for `dbFetch()` calls `fetch()` so that it is compatible with existing code. Modern backends should implement for `dbFetch()` only.

Value

`dbFetch()` always returns a [data.frame](#) with as many rows as records were fetched and as many columns as fields in the result set, even if the result is a single value or has one or zero rows.

See Also

Close the result set with [dbClearResult\(\)](#) as soon as you finish retrieving the records you want.

Other `DBIResult` generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbColumnInfo\(\)](#), [dbGetInfo\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbGetInfo,DatabaseConnectorConnection-method
Get DBMS metadata

Description

Retrieves information on objects of class [DBIDriver](#), [DBIConnection](#) or [DBIResult](#).

Usage

```
## S4 method for signature 'DatabaseConnectorConnection'
dbGetInfo(dbObj, ...)
```

Arguments

dbObj	An object inheriting from DBObject , i.e. DBIDriver , DBIConnection , or a DBIResult
...	Other arguments to methods.

Value

For objects of class [DBIDriver](#), dbGetInfo() returns a named list that contains at least the following components:

- `driver.version`: the package version of the DBI backend,
- `client.version`: the version of the DBMS client library.

For objects of class [DBIConnection](#), dbGetInfo() returns a named list that contains at least the following components:

- `db.version`: version of the database server,
- `dbname`: database name,
- `username`: username to connect to the database,
- `host`: hostname of the database server,
- `port`: port on the database server. It must not contain a `password` component. Components that are not applicable should be set to NA.

For objects of class [DBIResult](#), dbGetInfo() returns a named list that contains at least the following components:

- `statement`: the statement used with [dbSendQuery\(\)](#) or [dbExecute\(\)](#), as returned by [dbGetStatement\(\)](#),
- `row.count`: the number of rows fetched so far (for queries), as returned by [dbGetRowCount\(\)](#),
- `rows.affected`: the number of rows affected (for statements), as returned by [dbGetRowsAffected\(\)](#)
- `has.completed`: a logical that indicates if the query or statement has completed, as returned by [dbHasCompleted\(\)](#).

See Also

Other DBIDriver generics: [DBIDriver-class](#), [dbCanConnect\(\)](#), [dbConnect\(\)](#), [dbDataType\(\)](#), [dbDriver\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListConnections\(\)](#)

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbGetInfo,DatabaseConnectorDriver-method

Get DBMS metadata

Description

Retrieves information on objects of class [DBIDriver](#), [DBIConnection](#) or [DBIResult](#).

Usage

```
## S4 method for signature 'DatabaseConnectorDriver'
dbGetInfo(dbObj, ...)
```

Arguments

<code>dbObj</code>	An object inheriting from DBObject , i.e. DBIDriver , DBIConnection , or a DBIResult
<code>...</code>	Other arguments to methods.

Value

For objects of class [DBIDriver](#), `dbGetInfo()` returns a named list that contains at least the following components:

- `driver.version`: the package version of the DBI backend,
- `client.version`: the version of the DBMS client library.

For objects of class [DBIConnection](#), `dbGetInfo()` returns a named list that contains at least the following components:

- `db.version`: version of the database server,
- `dbname`: database name,
- `username`: username to connect to the database,
- `host`: hostname of the database server,
- `port`: port on the database server. It must not contain a password component. Components that are not applicable should be set to NA.

For objects of class [DBIResult](#), `dbGetInfo()` returns a named list that contains at least the following components:

- `statement`: the statement used with [dbSendQuery\(\)](#) or [dbExecute\(\)](#), as returned by [dbGetStatement\(\)](#),
- `row.count`: the number of rows fetched so far (for queries), as returned by [dbGetRowCount\(\)](#),
- `rows.affected`: the number of rows affected (for statements), as returned by [dbGetRowsAffected\(\)](#)
- `has.completed`: a logical that indicates if the query or statement has completed, as returned by [dbHasCompleted\(\)](#).

See Also

Other DBIDriver generics: [DBIDriver-class](#), [dbCanConnect\(\)](#), [dbConnect\(\)](#), [dbDataType\(\)](#), [dbDriver\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListConnections\(\)](#)

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbGetQuery,DatabaseConnectorConnection,character-method

Send query, retrieve results and then clear result set

Description

Returns the result of a query as a data frame. `dbGetQuery()` comes with a default implementation (which should work with most backends) that calls [dbSendQuery\(\)](#), then [dbFetch\(\)](#), ensuring that the result is always free'd by [dbClearResult\(\)](#). For retrieving chunked/paged results or for passing query parameters, see [dbSendQuery\(\)](#), in particular the "The data retrieval flow" section.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbGetQuery(conn, statement, translate = TRUE, ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by dbConnect() .
<code>statement</code>	a character string containing SQL.
<code>translate</code>	Translate the query using <code>SqlRender?</code>
<code>...</code>	Other parameters passed on to methods.

Details

This method is for SELECT queries only (incl. other SQL statements that return a SELECT-alike result, e. g. execution of a stored procedure or data manipulation queries like INSERT INTO ... RETURNING ...). To execute a stored procedure that does not return a result set, use [dbExecute\(\)](#).

Some backends may support data manipulation statements through this method for compatibility reasons. However, callers are strongly advised to use [dbExecute\(\)](#) for data manipulation statements.

Value

`dbGetQuery()` always returns a [data.frame](#) with as many rows as records were fetched and as many columns as fields in the result set, even if the result is a single value or has one or zero rows.

See Also

For updates: [dbSendStatement\(\)](#) and [dbExecute\(\)](#).

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

dbGetRowCount,DatabaseConnectorDbiResult-method

The number of rows fetched so far

Description

Returns the total number of rows actually fetched with calls to [dbFetch\(\)](#) for this result set.

Usage

```
## S4 method for signature 'DatabaseConnectorDbiResult'
dbGetRowCount(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

`dbGetRowCount()` returns a scalar number (integer or numeric), the number of rows fetched so far. After calling [dbSendQuery\(\)](#), the row count is initially zero. After a call to [dbFetch\(\)](#) without limit, the row count matches the total number of rows returned. Fetching a limited number of rows increases the number of rows by the number of rows returned, even if fetching past the end of the result set. For queries with an empty result set, zero is returned even after fetching. For data manipulation statements issued with [dbSendStatement\(\)](#), zero is returned before and after calling [dbFetch\(\)](#).

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbGetRowCount,DatabaseConnectorJdbcResult-method

The number of rows fetched so far

Description

Returns the total number of rows actually fetched with calls to [dbFetch\(\)](#) for this result set.

Usage

```
## S4 method for signature 'DatabaseConnectorJdbcResult'  
dbGetRowCount(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

`dbGetRowCount()` returns a scalar number (integer or numeric), the number of rows fetched so far. After calling [dbSendQuery\(\)](#), the row count is initially zero. After a call to [dbFetch\(\)](#) without limit, the row count matches the total number of rows returned. Fetching a limited number of rows increases the number of rows by the number of rows returned, even if fetching past the end of the result set. For queries with an empty result set, zero is returned even after fetching. For data manipulation statements issued with [dbSendStatement\(\)](#), zero is returned before and after calling [dbFetch\(\)](#).

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbGetRowsAffected,DatabaseConnectorDbiResult-method*The number of rows affected***Description**

This method returns the number of rows that were added, deleted, or updated by a data manipulation statement.

Usage

```
## S4 method for signature 'DatabaseConnectorDbiResult'
dbGetRowsAffected(res, ...)
```

Arguments

- | | |
|-----|-------------------------------------------------------|
| res | An object inheriting from DBIResult . |
| ... | Other arguments passed on to methods. |

Value

`dbGetRowsAffected()` returns a scalar number (integer or numeric), the number of rows affected by a data manipulation statement issued with [dbSendStatement\(\)](#). The value is available directly after the call and does not change after calling [dbFetch\(\)](#). For queries issued with [dbSendQuery\(\)](#), zero is returned before and after the call to [dbFetch\(\)](#).

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowCount\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbGetRowsAffected,DatabaseConnectorJdbcResult-method*The number of rows affected***Description**

This method returns the number of rows that were added, deleted, or updated by a data manipulation statement.

Usage

```
## S4 method for signature 'DatabaseConnectorJdbcResult'
dbGetRowsAffected(res, ...)
```

Arguments

- | | |
|-----|-------------------------------------------------------|
| res | An object inheriting from DBIResult . |
| ... | Other arguments passed on to methods. |

Value

`dbGetRowsAffected()` returns a scalar number (integer or numeric), the number of rows affected by a data manipulation statement issued with `dbSendStatement()`. The value is available directly after the call and does not change after calling `dbFetch()`. For queries issued with `dbSendQuery()`, zero is returned before and after the call to `dbFetch()`.

See Also

Other DBIResult generics: `DBIResult-class`, `dbBind()`, `dbClearResult()`, `dbColumnInfo()`, `dbFetch()`, `dbGetInfo()`, `dbGetRowCount()`, `dbGetStatement()`, `dbHasCompleted()`, `dbIsReadOnly()`, `dbIsValid()`, `dbQuoteIdentifier()`, `dbQuoteLiteral()`, `dbQuoteString()`, `dbUnquoteIdentifier()`

dbGetStatement,DatabaseConnectorDbiResult-method

Get the statement associated with a result set

Description

Returns the statement that was passed to `dbSendQuery()` or `dbSendStatement()`.

Usage

```
## S4 method for signature 'DatabaseConnectorDbiResult'  
dbGetStatement(res, ...)
```

Arguments

<code>res</code>	An object inheriting from <code>DBIResult</code> .
<code>...</code>	Other arguments passed on to methods.

Value

`dbGetStatement()` returns a string, the query used in either `dbSendQuery()` or `dbSendStatement()`.

See Also

Other DBIResult generics: `DBIResult-class`, `dbBind()`, `dbClearResult()`, `dbColumnInfo()`, `dbFetch()`, `dbGetInfo()`, `dbGetRowCount()`, `dbGetRowsAffected()`, `dbHasCompleted()`, `dbIsReadOnly()`, `dbIsValid()`, `dbQuoteIdentifier()`, `dbQuoteLiteral()`, `dbQuoteString()`, `dbUnquoteIdentifier()`

dbGetStatement,DatabaseConnectorJdbcResult-method
Get the statement associated with a result set

Description

Returns the statement that was passed to [dbSendQuery\(\)](#) or [dbSendStatement\(\)](#).

Usage

```
## S4 method for signature 'DatabaseConnectorJdbcResult'
dbGetStatement(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

`dbGetStatement()` returns a string, the query used in either [dbSendQuery\(\)](#) or [dbSendStatement\(\)](#).

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbHasCompleted,DatabaseConnectorDbiResult-method
Completion status

Description

This method returns if the operation has completed. A SELECT query is completed if all rows have been fetched. A data manipulation statement is always completed.

Usage

```
## S4 method for signature 'DatabaseConnectorDbiResult'
dbHasCompleted(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

`dbHasCompleted()` returns a logical scalar. For a query initiated by `dbSendQuery()` with non-empty result set, `dbHasCompleted()` returns FALSE initially and TRUE after calling `dbFetch()` without limit. For a query initiated by `dbSendStatement()`, `dbHasCompleted()` always returns TRUE.

See Also

Other DBIResult generics: `DBIResult-class`, `dbBind()`, `dbClearResult()`, `dbColumnInfo()`, `dbFetch()`, `dbGetInfo()`, `dbGetRowCount()`, `dbGetRowsAffected()`, `dbGetStatement()`, `dbIsReadOnly()`, `dbIsValid()`, `dbQuoteIdentifier()`, `dbQuoteLiteral()`, `dbQuoteString()`, `dbUnquoteIdentifier()`

dbHasCompleted,DatabaseConnectorJdbcResult-method

Completion status

Description

This method returns if the operation has completed. A SELECT query is completed if all rows have been fetched. A data manipulation statement is always completed.

Usage

```
## S4 method for signature 'DatabaseConnectorJdbcResult'
dbHasCompleted(res, ...)
```

Arguments

<code>res</code>	An object inheriting from <code>DBIResult</code> .
<code>...</code>	Other arguments passed on to methods.

Value

`dbHasCompleted()` returns a logical scalar. For a query initiated by `dbSendQuery()` with non-empty result set, `dbHasCompleted()` returns FALSE initially and TRUE after calling `dbFetch()` without limit. For a query initiated by `dbSendStatement()`, `dbHasCompleted()` always returns TRUE.

See Also

Other DBIResult generics: `DBIResult-class`, `dbBind()`, `dbClearResult()`, `dbColumnInfo()`, `dbFetch()`, `dbGetInfo()`, `dbGetRowCount()`, `dbGetRowsAffected()`, `dbGetStatement()`, `dbIsReadOnly()`, `dbIsValid()`, `dbQuoteIdentifier()`, `dbQuoteLiteral()`, `dbQuoteString()`, `dbUnquoteIdentifier()`

dbIsValid,DatabaseConnectorDbiConnection-method
Is this DBMS object still valid?

Description

This generic tests whether a database object is still valid (i.e. it hasn't been disconnected or cleared).

Usage

```
## S4 method for signature 'DatabaseConnectorDbiConnection'
dbIsValid(dbObj, ...)
```

Arguments

dbObj	An object inheriting from DBObject , i.e. DBIDriver , DBIConnection , or a DBIResult
...	Other arguments to methods.

Value

`dbIsValid()` returns a logical scalar, TRUE if the object specified by `dbObj` is valid, FALSE otherwise. A [DBIConnection](#) object is initially valid, and becomes invalid after disconnecting with [dbDisconnect\(\)](#). For an invalid connection object (e.g., for some drivers if the object is saved to a file and then restored), the method also returns FALSE. A [DBIResult](#) object is valid after a call to [dbSendQuery\(\)](#), and stays valid even after all rows have been fetched; only clearing it with [dbClearResult\(\)](#) invalidates it. A [DBIResult](#) object is also valid after a call to [dbSendStatement\(\)](#), and stays valid after querying the number of rows affected; only clearing it with [dbClearResult\(\)](#) invalidates it. If the connection to the database system is dropped (e.g., due to connectivity problems, server failure, etc.), `dbIsValid()` should return FALSE. This is not tested automatically.

See Also

Other [DBIDriver](#) generics: [DBIDriver-class](#), [dbCanConnect\(\)](#), [dbConnect\(\)](#), [dbDataType\(\)](#), [dbDriver\(\)](#), [dbGetInfo\(\)](#), [dbIsReadOnly\(\)](#), [dbListConnections\(\)](#)

Other [DBIConnection](#) generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

Other [DBIResult](#) generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

dbIsValid,DatabaseConnectorJdbcConnection-method
Is this DBMS object still valid?

Description

This generic tests whether a database object is still valid (i.e. it hasn't been disconnected or cleared).

Usage

```
## S4 method for signature 'DatabaseConnectorJdbcConnection'  
dbIsValid(dbObj, ...)
```

Arguments

dbObj	An object inheriting from DBObject , i.e. DBIDriver , DBIConnection , or a DBIResult
...	Other arguments to methods.

Value

`dbIsValid()` returns a logical scalar, TRUE if the object specified by `dbObj` is valid, FALSE otherwise. A [DBIConnection](#) object is initially valid, and becomes invalid after disconnecting with [dbDisconnect\(\)](#). For an invalid connection object (e.g., for some drivers if the object is saved to a file and then restored), the method also returns FALSE. A [DBIResult](#) object is valid after a call to [dbSendQuery\(\)](#), and stays valid even after all rows have been fetched; only clearing it with [dbClearResult\(\)](#) invalidates it. A [DBIResult](#) object is also valid after a call to [dbSendStatement\(\)](#), and stays valid after querying the number of rows affected; only clearing it with [dbClearResult\(\)](#) invalidates it. If the connection to the database system is dropped (e.g., due to connectivity problems, server failure, etc.), `dbIsValid()` should return FALSE. This is not tested automatically.

See Also

Other [DBIDriver](#) generics: [DBIDriver-class](#), [dbCanConnect\(\)](#), [dbConnect\(\)](#), [dbDataType\(\)](#), [dbDriver\(\)](#), [dbGetInfo\(\)](#), [dbIsReadOnly\(\)](#), [dbListConnections\(\)](#)

Other [DBIConnection](#) generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

Other [DBIResult](#) generics: [DBIResult-class](#), [dbBind\(\)](#), [dbClearResult\(\)](#), [dbColumnInfo\(\)](#), [dbFetch\(\)](#), [dbGetInfo\(\)](#), [dbGetRowCount\(\)](#), [dbGetRowsAffected\(\)](#), [dbGetStatement\(\)](#), [dbHasCompleted\(\)](#), [dbIsReadOnly\(\)](#), [dbQuoteIdentifier\(\)](#), [dbQuoteLiteral\(\)](#), [dbQuoteString\(\)](#), [dbUnquoteIdentifier\(\)](#)

`dbListFields`,*DatabaseConnectorConnection*,character-method

List field names of a remote table

Description

Returns the field names of a remote table as a character vector.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbListFields(conn, name, databaseSchema = NULL, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. <code>Id(schema = "my_schema", table = "table_name")</code> • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. <code>SQL('\"my_schema\".\"table_name\"')</code>
databaseSchema	The name of the database schema. See details for platform-specific details.
...	Other parameters passed on to methods.

Details

The `databaseSchema` argument is interpreted differently according to the different platforms: SQL Server and PDW: The `databaseSchema` schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the `databaseSchema` should specify the database. Oracle: The `databaseSchema` should specify the Oracle 'user'. All other : The `databaseSchema` should specify the schema.

Value

`dbListFields()` returns a character vector that enumerates all fields in the table in the correct order. This also works for temporary tables if supported by the database. The returned names are suitable for quoting with `dbQuoteIdentifier()`.

See Also

[dbColumnInfo\(\)](#) to get the type of the fields.

Other `DBIConnection` generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

dbListTables,DatabaseConnectorConnection-method
List remote tables

Description

Returns the unquoted names of remote tables accessible through this connection. This should include views and temporary objects, but not all database backends (in particular **RMariaDB** and **RMySQL**) support this.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection'  
dbListTables(conn, databaseSchema = NULL, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
databaseSchema	The name of the database schema. See details for platform-specific details.
...	Not used

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the databaseSchema should specify the database. Oracle: The databaseSchema should specify the Oracle 'user'. All other : The databaseSchema should specify the schema.

Value

`dbListTables()` returns a character vector that enumerates all tables and views in the database. Tables added with [dbWriteTable\(\)](#) are part of the list. As soon a table is removed from the database, it is also removed from the list of database tables.

The same applies to temporary tables if supported by the database.

The returned names are suitable for quoting with [dbQuoteIdentifier\(\)](#).

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

dbms	<i>Get the database platform from a connection</i>
------	----------------------------------------------------

Description

The SqlRender package provides functions that translate SQL from OHDSI-SQL to a target SQL dialect. These function need the name of the database platform to translate to. The dbms function returns the dbms for any DBI connection that can be passed along to SqlRender translation functions (see example).

Usage

```
dbms(connection)
```

Arguments

connection	The connection to the database server created using either connect() or dbConnect() .
------------	-----------------------------------------------------------------------------------------------------------------------

Value

The name of the database (dbms) used by SqlRender

Examples

```
library(DatabaseConnector)
con <- connect(dbms = "sqlite", server = ":memory:")
dbms(con)
#> [1] "sqlite"
SqlRender::translate("DATEADD(d, 365, dateColumn)", targetDialect = dbms(con))
#> "CAST(STRFTIME('%s', DATETIME(dateColumn, 'unixepoch', (365)||' days')) AS REAL)"
disconnect(con)
```

Description

Reads a database table to a data frame, optionally converting a column to row names and converting the column names to valid R identifiers.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbReadTable(
  conn,
  name,
  databaseSchema = NULL,
  oracleTempSchema = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  ...
)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. Id(schema = "my_schema", table = "table_name") • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. SQL(''my_schema''. "table_name'')
databaseSchema	The name of the database schema. See details for platform-specific details.
oracleTempSchema	<small>DEPRECATED: use tempEmulationSchema instead.</small>
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
...	Other parameters passed on to methods.

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the databaseSchema should specify the database. Oracle: The databaseSchema should specify the Oracle 'user'. All other : The databaseSchema should specify the schema.

Value

`dbReadTable()` returns a data frame that contains the complete data from the remote table, effectively the result of calling [dbGetQuery\(\)](#) with `SELECT * FROM <name>`.

An empty table is returned as a data frame with zero rows.

The presence of [rownames](#) depends on the `row.names` argument, see [sqlColumnToRownames\(\)](#) for details:

- If FALSE or NULL, the returned data frame doesn't have row names.
- If TRUE, a column named "row_names" is converted to row names.
- If NA, a column named "row_names" is converted to row names if it exists, otherwise no translation occurs.
- If a string, this specifies the name of the column in the remote table that contains the row names.

The default is `row.names = FALSE`.

If the database supports identifiers with special characters, the columns in the returned data frame are converted to valid R identifiers if the `check.names` argument is TRUE, If `check.names = FALSE`, the returned table has non-syntactic column names without quotes.

See Also

Other DBIConnection generics: `DBIConnection-class`, `dbAppendTable()`, `dbCreateTable()`, `dbDataType()`, `dbDisconnect()`, `dbExecute()`, `dbExistsTable()`, `dbGetException()`, `dbGetInfo()`, `dbGetQuery()`, `dbIsReadOnly()`, `dbIsValid()`, `dbListFields()`, `dbListObjects()`, `dbListResults()`, `dbListTables()`, `dbRemoveTable()`, `dbSendQuery()`, `dbSendStatement()`, `dbWriteTable()`

`dbRemoveTable,DatabaseConnectorConnection,ANY-method`
Remove a table from the database

Description

Remove a remote table (e.g., created by `dbWriteTable()`) from the database.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,ANY'
dbRemoveTable(
  conn,
  name,
  databaseSchema = NULL,
  oracleTempSchema = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  ...
)
```

Arguments

<code>conn</code>	A <code>DBIConnection</code> object, as returned by <code>dbConnect()</code> .
<code>name</code>	The table name, passed on to <code>dbQuoteIdentifier()</code> . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to <code>Id()</code> with components to the fully qualified table name, e.g. <code>Id(schema = "my_schema", table = "table_name")</code> • a call to <code>SQL()</code> with the quoted and fully qualified table name given verbatim, e.g. <code>SQL(''my_schema''. "table_name"')</code>
<code>databaseSchema</code>	The name of the database schema. See details for platform-specific details.
<code>oracleTempSchema</code>	DEPRECATED: use <code>tempEmulationSchema</code> instead.
<code>tempEmulationSchema</code>	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
<code>...</code>	Other parameters passed on to methods.

Details

The `databaseSchema` argument is interpreted differently according to the different platforms: SQL Server and PDW: The `databaseSchema` schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the `databaseSchema` should specify the database. Oracle: The `databaseSchema` should specify the Oracle 'user'. All other : The `databaseSchema` should specify the schema.

Value

`dbRemoveTable()` returns TRUE, invisibly.

See Also

Other DBIConnection generics: `DBIConnection-class`, `dbAppendTable()`, `dbCreateTable()`, `dbDataType()`, `dbDisconnect()`, `dbExecute()`, `dbExistsTable()`, `dbGetException()`, `dbGetInfo()`, `dbGetQuery()`, `dbIsReadOnly()`, `dbIsValid()`, `dbListFields()`, `dbListObjects()`, `dbListResults()`, `dbListTables()`, `dbReadTable()`, `dbSendQuery()`, `dbSendStatement()`, `dbWriteTable()`

`dbSendQuery,DatabaseConnectorDbiConnection,character-method`

Execute a query on a given database connection

Description

The `dbSendQuery()` method only submits and synchronously executes the SQL query to the database engine. It does *not* extract any records — for that you need to use the `dbFetch()` method, and then you must call `dbClearResult()` when you finish fetching the records you need. For interactive use, you should almost always prefer `dbGetQuery()`.

Usage

```
## S4 method for signature 'DatabaseConnectorDbiConnection,character'
dbSendQuery(conn, statement, translate = TRUE, ...)
```

Arguments

<code>conn</code>	A <code>DBIConnection</code> object, as returned by <code>dbConnect()</code> .
<code>statement</code>	a character string containing SQL.
<code>translate</code>	Translate the query using <code>SqlRender?</code>
<code>...</code>	Other parameters passed on to methods.

Details

This method is for SELECT queries only. Some backends may support data manipulation queries through this method for compatibility reasons. However, callers are strongly encouraged to use `dbSendStatement()` for data manipulation statements.

The query is submitted to the database server and the DBMS executes it, possibly generating vast amounts of data. Where these data live is driver-specific: some drivers may choose to leave the output on the server and transfer them piecemeal to R, others may transfer all the data to the client – but not necessarily to the memory that R manages. See individual drivers’ `dbSendQuery()` documentation for details.

Value

`dbSendQuery()` returns an S4 object that inherits from `DBIResult`. The result set can be used with `dbFetch()` to extract records. Once you have finished using a result, make sure to clear it with `dbClearResult()`.

See Also

For updates: `dbSendStatement()` and `dbExecute()`.

Other DBIConnection generics: `DBIConnection-class`, `dbAppendTable()`, `dbCreateTable()`, `dbDataType()`, `dbDisconnect()`, `dbExecute()`, `dbExistsTable()`, `dbGetException()`, `dbGetInfo()`, `dbGetQuery()`, `dbIsReadOnly()`, `dbIsValid()`, `dbListFields()`, `dbListObjects()`, `dbListResults()`, `dbListTables()`, `dbReadTable()`, `dbRemoveTable()`, `dbSendStatement()`, `dbWriteTable()`

`dbSendQuery,DatabaseConnectorJdbcConnection,character-method`

Execute a query on a given database connection

Description

The `dbSendQuery()` method only submits and synchronously executes the SQL query to the database engine. It does *not* extract any records — for that you need to use the `dbFetch()` method, and then you must call `dbClearResult()` when you finish fetching the records you need. For interactive use, you should almost always prefer `dbGetQuery()`.

Usage

```
## S4 method for signature 'DatabaseConnectorJdbcConnection,character'
dbSendQuery(conn, statement, translate = TRUE, ...)
```

Arguments

<code>conn</code>	A <code>DBIConnection</code> object, as returned by <code>dbConnect()</code> .
<code>statement</code>	a character string containing SQL.
<code>translate</code>	Translate the query using <code>SqlRender</code> ?
...	Other parameters passed on to methods.

Details

This method is for SELECT queries only. Some backends may support data manipulation queries through this method for compatibility reasons. However, callers are strongly encouraged to use `dbSendStatement()` for data manipulation statements.

The query is submitted to the database server and the DBMS executes it, possibly generating vast amounts of data. Where these data live is driver-specific: some drivers may choose to leave the output on the server and transfer them piecemeal to R, others may transfer all the data to the client – but not necessarily to the memory that R manages. See individual drivers' `dbSendQuery()` documentation for details.

Value

`dbSendQuery()` returns an S4 object that inherits from `DBIResult`. The result set can be used with `dbFetch()` to extract records. Once you have finished using a result, make sure to clear it with `dbClearResult()`.

See Also

For updates: [dbSendStatement\(\)](#) and [dbExecute\(\)](#).

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendStatement\(\)](#), [dbWriteTable\(\)](#)

dbSendStatement,DatabaseConnectorConnection,character-method

Execute a data manipulation statement on a given database connection

Description

The `dbSendStatement()` method only submits and synchronously executes the SQL data manipulation statement (e.g., UPDATE, DELETE, INSERT INTO, DROP TABLE, ...) to the database engine. To query the number of affected rows, call [dbGetRowsAffected\(\)](#) on the returned result object. You must also call [dbClearResult\(\)](#) after that. For interactive use, you should almost always prefer [dbExecute\(\)](#).

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'  
dbSendStatement(conn, statement, translate = TRUE, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
statement	a character string containing SQL.
translate	Translate the query using <code>SqlRender?</code>
...	Other parameters passed on to methods.

Details

`dbSendStatement()` comes with a default implementation that simply forwards to [dbSendQuery\(\)](#), to support backends that only implement the latter.

Value

`dbSendStatement()` returns an S4 object that inherits from [DBIResult](#). The result set can be used with [dbGetRowsAffected\(\)](#) to determine the number of rows affected by the query. Once you have finished using a result, make sure to clear it with [dbClearResult\(\)](#).

See Also

For queries: [dbSendQuery\(\)](#) and [dbGetQuery\(\)](#).

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbWriteTable\(\)](#)

dbUnloadDriver , DatabaseConnectorDriver-method
Load and unload database drivers

Description

These methods are deprecated, please consult the documentation of the individual backends for the construction of driver instances.

`dbDriver()` is a helper method used to create a new driver object given the name of a database or the corresponding R package. It works through convention: all DBI-extending packages should provide an exported object with the same name as the package. `dbDriver()` just looks for this object in the right places: if you know what database you are connecting to, you should call the function directly.

`dbUnloadDriver()` is not implemented for modern backends.

Usage

```
## S4 method for signature 'DatabaseConnectorDriver'
dbUnloadDriver(drv, ...)
```

Arguments

<code>drv</code>	an object that inherits from <code>DBIDriver</code> as created by <code>dbDriver</code> .
<code>...</code>	any other arguments are passed to the driver <code>drvName</code> .

Details

The client part of the database communication is initialized (typically dynamically loading C code, etc.) but note that connecting to the database engine itself needs to be done through calls to `dbConnect`.

Value

In the case of `dbDriver`, an driver object whose class extends `DBIDriver`. This object may be used to create connections to the actual DBMS engine.

In the case of `dbUnloadDriver`, a logical indicating whether the operation succeeded or not.

See Also

Other `DBIDriver` generics: [DBIDriver-class](#), [dbCanConnect\(\)](#), [dbConnect\(\)](#), [dbDataType\(\)](#), [dbGetInfo\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListConnections\(\)](#)

Other `DBIDriver` generics: [DBIDriver-class](#), [dbCanConnect\(\)](#), [dbConnect\(\)](#), [dbDataType\(\)](#), [dbGetInfo\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListConnections\(\)](#)

dbWriteTable, DatabaseConnectorConnection, ANY-method
Copy data frames to database tables

Description

Writes, overwrites or appends a data frame to a database table, optionally converting row names to a column and specifying SQL data types for fields.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,ANY'
dbWriteTable(
  conn,
  name,
  value,
  databaseSchema = NULL,
  overwrite = FALSE,
  append = FALSE,
  temporary = FALSE,
  oracleTempSchema = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  ...
)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	The table name, passed on to dbQuoteIdentifier() . Options are: <ul style="list-style-type: none"> • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. Id(schema = "my_schema", table = "table_name") • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. SQL(''my_schema''. "table_name'')
value	a data.frame (or coercible to data.frame).
databaseSchema	The name of the database schema. See details for platform-specific details.
overwrite	Overwrite an existing table (if exists)?
append	Append to existing table?
temporary	Should the table created as a temp table?
oracleTempSchema	DEPRECATED: use tempEmulationSchema instead.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
...	Other parameters passed on to methods.

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the databaseSchema should specify the database. Oracle: The databaseSchema should specify the Oracle 'user'. All other : The databaseSchema should specify the schema.

Value

`dbWriteTable()` returns TRUE, invisibly.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbAppendTable\(\)](#), [dbCreateTable\(\)](#), [dbDataType\(\)](#), [dbDisconnect\(\)](#), [dbExecute\(\)](#), [dbExistsTable\(\)](#), [dbGetException\(\)](#), [dbGetInfo\(\)](#), [dbGetQuery\(\)](#), [dbIsReadOnly\(\)](#), [dbIsValid\(\)](#), [dbListFields\(\)](#), [dbListObjects\(\)](#), [dbListResults\(\)](#), [dbListTables\(\)](#), [dbReadTable\(\)](#), [dbRemoveTable\(\)](#), [dbSendQuery\(\)](#), [dbSendStatement\(\)](#)

`disconnect`

Disconnect from the server

Description

Close the connection to the server.

Usage

```
disconnect(connection)
```

Arguments

`connection` The connection to the database server created using either [connect\(\)](#) or [dbConnect\(\)](#).

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost",
  user = "root",
  password = "blah"
)
conn <- connect(connectionDetails)
count <- querySql(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

## End(Not run)
```

downloadJdbcDrivers *Download DatabaseConnector JDBC Jar files*

Description

Download the DatabaseConnector JDBC drivers from <https://ohdsi.github.io/DatabaseConnectorJars/>

Usage

```
downloadJdbcDrivers(  
    dbms,  
    pathToDriver = Sys.getenv("DATABASECONNECTOR_JAR_FOLDER"),  
    method = "auto",  
    ...  
)
```

Arguments

dbms	The type of DBMS to download Jar files for. <ul style="list-style-type: none">• "postgresql" for PostgreSQL• "redshift" for Amazon Redshift• "sql server", "pdw" or "synapse" for Microsoft SQL Server• "oracle" for Oracle• "spark" for Spark• "snowflake" for Snowflake• "bigquery" for Google BigQuery• "all" for all aforementioned platforms
pathToDriver	The full path to the folder where the JDBC driver .jar files should be downloaded to. By default the value of the environment variable "DATABASECONNECTOR_JAR_FOLDER" is used.
method	The method used for downloading files. See ?download.file for details and options.
...	Further arguments passed on to download.file.

Details

The following versions of the JDBC drivers are currently used:

- PostgreSQL: V42.2.18
- RedShift: V2.1.0.9
- SQL Server: V9.2.0
- Oracle: V19.8
- Spark: V2.6.21
- Snowflake: V3.13.22
- BigQuery: v1.3.2.1003

Value

Invisibly returns the destination if the download was successful.

Examples

```
## Not run:
downloadJdbcDrivers("redshift")

## End(Not run)
```

dropEmulatedTempTables

Drop all emulated temp tables.

Description

On some DBMSs, like Oracle and BigQuery, DatabaseConnector through SqlRender emulates temp tables in a schema provided by the user. Ideally, these tables are deleted by the application / R script creating them, but for various reasons orphan temp tables may remain. This function drops all emulated temp tables created in this session only.

Usage

```
dropEmulatedTempTables(
  connection,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema")
)
```

Arguments

connection	The connection to the database server created using either connect() or dbConnect() .
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

Value

Invisibly returns the list of deleted emulated temp tables.

eoMonth	<i>Return the end of the month</i>
---------	------------------------------------

Description

This function is provided primarily to be used together with `dbplyr` when querying a database. It will also work in `dplyr` against data frames.

Usage

```
eoMonth(date)
```

Arguments

`date` A date in the month for which we need the end.

Value

The date of the last day of the month.

Examples

```
eoMonth(as.Date("2000-02-01"))
```

executeSql	<i>Execute SQL code</i>
------------	-------------------------

Description

This function executes SQL consisting of one or more statements.

Usage

```
executeSql(  
  connection,  
  sql,  
  profile = FALSE,  
  progressBar = !as.logical(Sys.getenv("TESTTHAT", unset = FALSE)),  
  reportOverallTime = TRUE,  
  errorReportFile = file.path(getwd(), "errorReportSql.txt"),  
  runAsBatch = FALSE  
)
```

Arguments

connection	The connection to the database server created using either <code>connect()</code> or <code>dbConnect()</code> .
sql	The SQL to be executed
profile	When true, each separate statement is written to file prior to sending to the server, and the time taken to execute a statement is displayed.
progressBar	When true, a progress bar is shown based on the statements in the SQL code.
reportOverallTime	When true, the function will display the overall time taken to execute all statements.
errorReportFile	The file where an error report will be written if an error occurs. Defaults to 'errorReportSql.txt' in the current working directory.
runAsBatch	When true the SQL statements are sent to the server as a single batch, and executed there. This will be faster if you have many small SQL statements, but there will be no progress bar, and no per-statement error messages. If the database platform does not support batched updates the query is executed without batching.

Details

This function splits the SQL in separate statements and sends it to the server for execution. If an error occurs during SQL execution, this error is written to a file to facilitate debugging. Optionally, a progress bar is shown and the total time taken to execute the SQL is displayed. Optionally, each separate SQL statement is written to file, and the execution time per statement is shown to aid in detecting performance issues.

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost",
  user = "root",
  password = "blah",
  schema = "cdm_v4"
)
conn <- connect(connectionDetails)
executeSql(conn, "CREATE TABLE x (k INT); CREATE TABLE y (k INT);")
disconnect(conn)

## End(Not run)
```

existsTable	<i>Does the table exist?</i>
-------------	------------------------------

Description

Checks whether a table exists. Accounts for surrounding escape characters. Case insensitive.

Usage

```
existsTable(connection, databaseSchema, tableName)
```

Arguments

- connection The connection to the database server created using either [connect\(\)](#) or [dbConnect\(\)](#).
databaseSchema The name of the database schema. See details for platform-specific details.
tableName The name of the table to check.

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the databaseSchema should specify the database. Oracle: The databaseSchema should specify the Oracle 'user'. All other : The databaseSchema should specify the schema.

Value

A logical value indicating whether the table exists.

extractQueryTimes	<i>Extract query times from a ParallelLogger log file</i>
-------------------	-----------------------------------------------------------

Description

When using the ParallelLogger default file logger, and using `options(LOG_DATABASECONNECTOR_SQL = TRUE)`, DatabaseConnector will log all SQL sent to the server, and the time to get a response.

This function parses the log file, producing a data frame with time per query.

Usage

```
extractQueryTimes(logFileName)
```

Arguments

- logFileName Name of the ParallelLogger log file. Assumes the file was created using the default file logger.

Value

A data frame with queries and their run times in milliseconds.

Examples

```
connection <- connect(dbms = "sqlite", server = ":memory:")
logFile <- tempfile(fileext = ".log")
ParallelLogger::addDefaultFileLogger(fileName = logFile, name = "MY_LOGGER")
options(LOG_DATABASECONNECTOR_SQL = TRUE)

executeSql(connection, "CREATE TABLE test (x INT);")
querySql(connection, "SELECT * FROM test;")

extractQueryTimes(logFile)

ParallelLogger::unregisterLogger("MY_LOGGER")
unlink(logFile)
disconnect(connection)
```

getAvailableJavaHeapSpace

Get available Java heap space

Description

For debugging purposes: get the available Java heap space.

Usage

```
getAvailableJavaHeapSpace()
```

Value

The Java heap space (in bytes).

getTableName

List all tables in a database schema.

Description

This function returns a list of all tables in a database schema.

Usage

```
getTableName(connection, databaseSchema = NULL, cast = "lower")
```

Arguments

connection	The connection to the database server created using either connect() or dbConnect() .
databaseSchema	The name of the database schema. See details for platform-specific details.
cast	Should the table names be cast to uppercase or lowercase before being returned? Valid options are "upper" , "lower" (default), "none" (no casting is done)

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the databaseSchema should specify the database. Oracle: The databaseSchema should specify the Oracle 'user'. All other : The databaseSchema should specify the schema.

Value

A character vector of table names.

inDatabaseSchema	<i>Refer to a table in a database schema</i>
------------------	----------------------------------------------

Description

Can be used with `dplyr::tbl()` to indicate a table in a specific database schema.

Usage

```
inDatabaseSchema(databaseSchema, table)
```

Arguments

databaseSchema The name of the database schema. See details for platform-specific details.

table The name of the table in the database schema.

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the databaseSchema should specify the database. Oracle: The databaseSchema should specify the Oracle 'user'. All other : The databaseSchema should specify the schema.

Value

An object representing the table and database schema.

insertTable	<i>Insert a table on the server</i>
-------------	-------------------------------------

Description

This function sends the data in a data frame to a table on the server. Either a new table is created, or the data is appended to an existing table.

Usage

```
insertTable(
  connection,
  databaseSchema = NULL,
  tableName,
  data,
  dropTableIfExists = TRUE,
  createTable = TRUE,
  tempTable = FALSE,
  oracleTempSchema = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  bulkLoad = Sys.getenv("DATABASE_CONNECTOR_BULK_UPLOAD"),
  useMppBulkLoad = Sys.getenv("USE_MPP_BULK_LOAD"),
  progressBar = FALSE,
  camelCaseToSnakeCase = FALSE
)
```

Arguments

connection	The connection to the database server created using either connect() or dbConnect() .
databaseSchema	The name of the database schema. See details for platform-specific details.
tableName	The name of the table where the data should be inserted.
data	The data frame containing the data to be inserted.
dropTableIfExists	Drop the table if the table already exists before writing?
createTable	Create a new table? If false, will append to existing table.
tempTable	Should the table created as a temp table?
oracleTempSchema	DEPRECATED: use tempEmulationSchema instead.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
bulkLoad	If using Redshift, PDW, Hive or Postgres, use more performant bulk loading techniques. Does not work for temp tables (except for HIVE). See Details for requirements for the various platforms.
useMppBulkLoad	DEPRECATED. Use bulkLoad instead.
progressBar	Show a progress bar when uploading?
camelCaseToSnakeCase	If TRUE, the data frame column names are assumed to use camelCase and are converted to snake_case before uploading.

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. Impala: the databaseSchema should specify the database. Oracle: The databaseSchema should specify the Oracle 'user'. All other : The databaseSchema should specify the schema.

This function sends the data in a data frame to a table on the server. Either a new table is created, or the data is appended to an existing table. NA values are inserted as null values in the database.

Bulk uploading:

Redshift: The MPP bulk loading relies upon the CloudyR S3 library to test a connection to an S3 bucket using AWS S3 credentials. Credentials are configured directly into the System Environment using the following keys: Sys.setenv("AWS_ACCESS_KEY_ID" = "some_access_key_id", "AWS_SECRET_ACCESS_KEY" = "some_secret_access_key", "AWS_DEFAULT_REGION" = "some_aws_region", "AWS_BUCKET_NAME" = "some_bucket_name", "AWS_OBJECT_KEY" = "some_object_key", "AWS_SSE_TYPE" = "server_side_encryption_type").

PDW: The MPP bulk loading relies upon the client having a Windows OS and the DWLoader exe installed, and the following permissions granted: –Grant BULK Load permissions - needed at a server level USE master; GRANT ADMINISTER BULK OPERATIONS TO user; –Grant Staging database permissions - we will use the user db. USE scratch; EXEC sp_addrolemember 'db_ddladmin', user; Set the R environment variable DWLOADER_PATH to the location of the binary.

PostgreSQL: Uses the 'psql' executable to upload. Set the POSTGRES_PATH environment variable to the Postgres binary path, e.g. 'C:/Program Files/PostgreSQL/11/bin' on Windows or '/Library/PostgreSQL/16/bin' on MacOs.

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(
  dbms = "mysql",
  server = "localhost",
  user = "root",
  password = "blah"
)
conn <- connect(connectionDetails)
data <- data.frame(x = c(1, 2, 3), y = c("a", "b", "c"))
insertTable(conn, "my_schema", "my_table", data)
disconnect(conn)

## bulk data insert with Redshift or PDW
connectionDetails <- createConnectionDetails(
  dbms = "redshift",
  server = "localhost",
  user = "root",
  password = "blah",
  schema = "cdm_v5"
)
conn <- connect(connectionDetails)
data <- data.frame(x = c(1, 2, 3), y = c("a", "b", "c"))
insertTable(
  connection = connection,
  databaseSchema = "scratch",
  tableName = "somedata",
```

```

data = data,
dropTableIfExists = TRUE,
createTable = TRUE,
tempTable = FALSE,
bulkLoad = TRUE
) # or, Sys.setenv("DATABASE_CONNECTOR_BULK_UPLOAD" = TRUE)

## End(Not run)

```

isSqlReservedWord*Test a character vector of SQL names for SQL reserved words***Description**

This function checks a character vector against a predefined list of reserved SQL words.

Usage

```
isSqlReservedWord(sqlNames, warn = FALSE)
```

Arguments

sqlNames	A character vector containing table or field names to check.
warn	(logical) Should a warn be thrown if invalid SQL names are found?

Value

A logical vector with length equal to sqlNames that is TRUE for each name that is reserved and FALSE otherwise

jdbcDrivers*How to download and use JDBC drivers for the various data platforms.***Description**

Below are instructions for downloading JDBC drivers for the various data platforms. Once downloaded use the `pathToDriver` argument in the [connect\(\)](#) or [createConnectionDetails\(\)](#) functions to point to the driver. Alternatively, you can set the 'DATABASECONNECTOR_JAR_FOLDER' environmental variable, for example in your .Renvironment file (recommended).

SQL Server, Oracle, PostgreSQL, PDW, Snowflake, Spark, RedShift, Azure Synapse, BigQuery

Use the [downloadJdbcDrivers\(\)](#) function to download these drivers from the OHDSI GitHub pages.

Netezza

Read the instructions [here](#) on how to obtain the Netezza JDBC driver.

Impala

Go to [Cloudera's site](#), pick your OS version, and click "GET IT NOW!". Register, and you should be able to download the driver.

SQLite

For SQLite we actually don't use a JDBC driver. Instead, we use the RSQLite package, which can be installed using `install.packages("RSQLite")`.

`lowLevelExecuteSql` *Execute SQL code*

Description

This function executes a single SQL statement.

Usage

```
lowLevelExecuteSql(connection, sql)
```

Arguments

<code>connection</code>	The connection to the database server created using either <code>connect()</code> or <code>dbConnect()</code> .
<code>sql</code>	The SQL to be executed

`lowLevelQuerySql` *Low level function for retrieving data to a data frame*

Description

This is the equivalent of the `querySql()` function, except no error report is written when an error occurs.

Usage

```
lowLevelQuerySql(  
  connection,  
  query,  
  datesAsString = FALSE,  
  integerAsNumeric = getOption("databaseConnectorIntegerAsNumeric", default = TRUE),  
  integer64AsNumeric = getOption("databaseConnectorInteger64AsNumeric", default = TRUE)  
)
```

Arguments

<code>connection</code>	The connection to the database server created using either connect() or dbConnect() .
<code>query</code>	The SQL statement to retrieve the data
<code>datesAsString</code>	Logical: Should dates be imported as character vectors, or should they be converted to R's date format?
<code>integerAsNumeric</code>	Logical: should 32-bit integers be converted to numeric (double) values? If FALSE 32-bit integers will be represented using R's native Integer class.
<code>integer64AsNumeric</code>	Logical: should 64-bit integers be converted to numeric (double) values? If FALSE 64-bit integers will be represented using <code>bit64::integer64</code> .

Details

Retrieves data from the database server and stores it in a data frame. Null values in the database are converted to NA values in R.

Value

A data frame containing the data retrieved from the server

lowLevelQuerySqlToAndromeda

Low level function for retrieving data to a local Andromeda object

Description

This is the equivalent of the [querySqlToAndromeda\(\)](#) function, except no error report is written when an error occurs.

Usage

```
lowLevelQuerySqlToAndromeda(
  connection,
  query,
  andromeda,
  andromedaTableName,
  datesAsString = FALSE,
  appendToTable = FALSE,
  snakeCaseToCamelCase = FALSE,
  integerAsNumeric = getOption("databaseConnectorIntegerAsNumeric", default = TRUE),
  integer64AsNumeric = getOption("databaseConnectorInteger64AsNumeric", default = TRUE)
)
```

Arguments

<code>connection</code>	The connection to the database server created using either connect() or dbConnect() .
<code>query</code>	The SQL statement to retrieve the data
<code>andromeda</code>	An open Andromeda object, for example as created using Andromeda::andromeda() .

andromedaTableName	The name of the table in the local Andromeda object where the results of the query will be stored.
datesAsString	Should dates be imported as character vectors, or should they be converted to R's date format?
appendToTable	If FALSE, any existing table in the Andromeda with the same name will be replaced with the new data. If TRUE, data will be appended to an existing table, assuming it has the exact same structure.
snakeCaseToCamelCase	If true, field names are assumed to use snake_case, and are converted to camelCase.
integerAsNumeric	Logical: should 32-bit integers be converted to numeric (double) values? If FALSE 32-bit integers will be represented using R's native Integer class.
integer64AsNumeric	Logical: should 64-bit integers be converted to numeric (double) values? If FALSE 64-bit integers will be represented using bit64::integer64.

Details

Retrieves data from the database server and stores it in a local Andromeda object. This allows very large data sets to be retrieved without running out of memory. Null values in the database are converted to NA values in R. If a table with the same name already exists in the local Andromeda object it is replaced.

Value

Invisibly returns the andromeda. The Andromeda object will have a table added with the query results.

month	<i>Extract the month from a date</i>
-------	--------------------------------------

Description

This function is provided primarily to be used together with dbplyr when querying a database. It will also work in dplyr against data frames.

Usage

```
month(date)
```

Arguments

date	The date.
------	-----------

Value

The month

Examples

```
month(as.Date("2000-02-01"))
```

querySql

Retrieve data to a data.frame

Description

This function sends SQL to the server, and returns the results.

Usage

```
querySql(
  connection,
  sql,
  errorReportFile = file.path(getwd(), "errorReportSql.txt"),
  snakeCaseToCamelCase = FALSE,
  integerAsNumeric = getOption("databaseConnectorIntegerAsNumeric", default = TRUE),
  integer64AsNumeric = getOption("databaseConnectorInteger64AsNumeric", default = TRUE)
)
```

Arguments

connection	The connection to the database server created using either connect() or dbConnect() .
sql	The SQL to be send.
errorReportFile	The file where an error report will be written if an error occurs. Defaults to 'errorReportSql.txt' in the current working directory.
snakeCaseToCamelCase	If true, field names are assumed to use snake_case, and are converted to camel-Case.
integerAsNumeric	Logical: should 32-bit integers be converted to numeric (double) values? If FALSE 32-bit integers will be represented using R's native Integer class.
integer64AsNumeric	Logical: should 64-bit integers be converted to numeric (double) values? If FALSE 64-bit integers will be represented using bit64::integer64.

Details

This function sends the SQL to the server and retrieves the results. If an error occurs during SQL execution, this error is written to a file to facilitate debugging. Null values in the database are converted to NA values in R.

Value

A data frame.

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost",
  user = "root",
  password = "blah",
  schema = "cdm_v4"
)
conn <- connect(connectionDetails)
count <- querySql(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

## End(Not run)
```

`querySqlToAndromeda` *Retrieves data to a local Andromeda object*

Description

This function sends SQL to the server, and returns the results in a local Andromeda object

Usage

```
querySqlToAndromeda(
  connection,
  sql,
  andromeda,
  andromedaTableName,
  errorReportFile = file.path(getwd(), "errorReportSql.txt"),
  snakeCaseToCamelCase = FALSE,
  appendToTable = FALSE,
  integerAsNumeric = getOption("databaseConnectorIntegerAsNumeric", default = TRUE),
  integer64AsNumeric = getOption("databaseConnectorInteger64AsNumeric", default = TRUE)
)
```

Arguments

<code>connection</code>	The connection to the database server created using either connect() or dbConnect() .
<code>sql</code>	The SQL to be sent.
<code>andromeda</code>	An open Andromeda object, for example as created using Andromeda::andromeda() .
<code>andromedaTableName</code>	The name of the table in the local Andromeda object where the results of the query will be stored.
<code>errorReportFile</code>	The file where an error report will be written if an error occurs. Defaults to 'errorReportSql.txt' in the current working directory.
<code>snakeCaseToCamelCase</code>	If true, field names are assumed to use <code>snake_case</code> , and are converted to <code>camelCase</code> .

appendToTable If FALSE, any existing table in the Andromeda with the same name will be replaced with the new data. If TRUE, data will be appended to an existing table, assuming it has the exact same structure.

integerAsNumeric
Logical: should 32-bit integers be converted to numeric (double) values? If FALSE 32-bit integers will be represented using R's native Integer class.

integer64AsNumeric
Logical: should 64-bit integers be converted to numeric (double) values? If FALSE 64-bit integers will be represented using `bit64::integer64`.

Details

Retrieves data from the database server and stores it in a local Andromeda object. This allows very large data sets to be retrieved without running out of memory. If an error occurs during SQL execution, this error is written to a file to facilitate debugging. Null values in the database are converted to NA values in R. If a table with the same name already exists in the local Andromeda object it is replaced.

Value

Invisibly returns the andromeda. The Andromeda object will have a table added with the query results.

Examples

```
## Not run:
andromeda <- Andromeda::andromeda()
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost",
  user = "root",
  password = "blah",
  schema = "cdm_v4"
)
conn <- connect(connectionDetails)
querySqlToAndromeda(
  connection = conn,
  sql = "SELECT * FROM person;",
  andromeda = andromeda,
  andromedaTableName = "foo"
)
disconnect(conn)

andromeda$foo

## End(Not run)
```

Description

This function renders, translates, and executes SQL consisting of one or more statements.

Usage

```
renderTranslateExecuteSql(  
  connection,  
  sql,  
  profile = FALSE,  
  progressBar = TRUE,  
  reportOverallTime = TRUE,  
  errorReportFile = file.path(getwd(), "errorReportSql.txt"),  
  runAsBatch = FALSE,  
  oracleTempSchema = NULL,  
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),  
  ...  
)
```

Arguments

connection	The connection to the database server created using either connect() or dbConnect() .
sql	The SQL to be executed
profile	When true, each separate statement is written to file prior to sending to the server, and the time taken to execute a statement is displayed.
progressBar	When true, a progress bar is shown based on the statements in the SQL code.
reportOverallTime	When true, the function will display the overall time taken to execute all statements.
errorReportFile	The file where an error report will be written if an error occurs. Defaults to 'errorReportSql.txt' in the current working directory.
runAsBatch	When true the SQL statements are sent to the server as a single batch, and executed there. This will be faster if you have many small SQL statements, but there will be no progress bar, and no per-statement error messages. If the database platform does not support batched updates the query is executed as ordinarily.
oracleTempSchema	DEPRECATED: use <code>tempEmulationSchema</code> instead.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
...	Parameters that will be used to render the SQL.

Details

This function calls the `render` and `translate` functions in the `SqlRender` package before calling [executeSql\(\)](#).

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost",
  user = "root",
  password = "blah",
  schema = "cdm_v4"
)
conn <- connect(connectionDetails)
renderTranslateExecuteSql(connection,
  sql = "SELECT * INTO #temp FROM @schema.person;",
  schema = "cdm_synpuf"
)
disconnect(conn)

## End(Not run)
```

renderTranslateQueryApplyBatched

Render, translate, and perform process to batches of data.

Description

This function renders, and translates SQL, sends it to the server, processes the data in batches with a call back function. Note that this function should perform a row-wise operation. This is designed to work with massive data that won't fit in to memory.

The batch sizes are determined by the java virtual machine and will depend on the data.

Usage

```
renderTranslateQueryApplyBatched(
  connection,
  sql,
  fun,
  args = list(),
  errorReportFile = file.path(getwd(), "errorReportSql.txt"),
  snakeCaseToCamelCase = FALSE,
  oracleTempSchema = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  integerAsNumeric = getOption("databaseConnectorIntegerAsNumeric", default = TRUE),
  integer64AsNumeric = getOption("databaseConnectorInteger64AsNumeric", default = TRUE),
  ...
)
```

Arguments

connection	The connection to the database server created using either connect() or dbConnect() .
sql	The SQL to be send.
fun	Function to apply to batch. Must take data.frame and integer position as parameters.

```

args           List of arguments to be passed to function call.
errorReportFile
  The file where an error report will be written if an error occurs. Defaults to
  'errorReportSql.txt' in the current working directory.
snakeCaseToCamelCase
  If true, field names are assumed to use snake_case, and are converted to camel-
  Case.
oracleTempSchema
  DEPRECATED: use tempEmulationSchema instead.
tempEmulationSchema
  Some database platforms like Oracle and Impala do not truly support temp ta-
  bles. To emulate temp tables, provide a schema with write privileges where
  temp tables can be created.
integerAsNumeric
  Logical: should 32-bit integers be converted to numeric (double) values? If
  FALSE 32-bit integers will be represented using R's native Integer class.
integer64AsNumeric
  Logical: should 64-bit integers be converted to numeric (double) values? If
  FALSE 64-bit integers will be represented using bit64::integer64.
...
  Parameters that will be used to render the SQL.

```

Details

This function calls the `render` and `translate` functions in the `SqlRender` package before calling [querySql\(\)](#).

Value

Invisibly returns a list of outputs from each call to the provided function.

Examples

```

## Not run:
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost",
  user = "root",
  password = "blah",
  schema = "cdm_v4"
)
connection <- connect(connectionDetails)

# First example: write data to a large CSV file:
filepath <- "myBigFile.csv"
writeBatchesToCsv <- function(data, position, ...) {
  write.csv(data, filepath, append = position != 1)
  return(NULL)
}
renderTranslateQueryApplyBatched(connection,
  "SELECT * FROM @schema.person;",
  schema = "cdm_synpuf",
  fun = writeBatchesToCsv
)

```

```

# Second example: write data to Andromeda
# (Alternative to querySqlToAndromeda if some local computation needs to be applied)
bigResults <- Andromeda::andromeda()
writeBatchesToAndromeda <- function(data, position, ...) {
  data$p <- EmpiricalCalibration::computeTraditionalP(data$logRr, data$logSeRr)
  if (position == 1) {
    bigResults$rrs <- data
  } else {
    Andromeda::appendToTable(bigResults$rrs, data)
  }
  return(NULL)
}
sql <- "SELECT target_id, comparator_id, log_rr, log_se_rr FROM @schema.my_results;"
renderTranslateQueryApplyBatched(connection,
  sql,
  fun = writeBatchesToAndromeda,
  schema = "my_results",
  snakeCaseToCamelCase = TRUE
)
disconnect(connection)

## End(Not run)

```

renderTranslateQuerySql*Render, translate, and query to data.frame***Description**

This function renders, and translates SQL, sends it to the server, and returns the results as a data.frame.

Usage

```

renderTranslateQuerySql(
  connection,
  sql,
  errorReportFile = file.path(getwd(), "errorReportSql.txt"),
  snakeCaseToCamelCase = FALSE,
  oracleTempSchema = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  integerAsNumeric = getOption("databaseConnectorIntegerAsNumeric", default = TRUE),
  integer64AsNumeric = getOption("databaseConnectorInteger64AsNumeric", default = TRUE),
  ...
)

```

Arguments

- | | |
|-------------------------|-----------------------------------------------------------------------------------------------------------------|
| <code>connection</code> | The connection to the database server created using either <code>connect()</code> or <code>dbConnect()</code> . |
| <code>sql</code> | The SQL to be send. |

```

errorReportFile
    The file where an error report will be written if an error occurs. Defaults to
    'errorReportSql.txt' in the current working directory.

snakeCaseToCamelCase
    If true, field names are assumed to use snake_case, and are converted to camel-
    Case.

oracleTempSchema
    DEPRECATED: use tempEmulationSchema instead.

tempEmulationSchema
    Some database platforms like Oracle and Impala do not truly support temp ta-
    bles. To emulate temp tables, provide a schema with write privileges where
    temp tables can be created.

integerAsNumeric
    Logical: should 32-bit integers be converted to numeric (double) values? If
    FALSE 32-bit integers will be represented using R's native Integer class.

integer64AsNumeric
    Logical: should 64-bit integers be converted to numeric (double) values? If
    FALSE 64-bit integers will be represented using bit64::integer64.

...
    Parameters that will be used to render the SQL.

```

Details

This function calls the `render` and `translate` functions in the `SqlRender` package before calling [querySql\(\)](#).

Value

A data frame.

Examples

```

## Not run:
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost",
  user = "root",
  password = "blah",
  schema = "cdm_v4"
)
conn <- connect(connectionDetails)
persons <- renderTranslatequerySql(conn,
  sql = "SELECT TOP 10 * FROM @schema.person",
  schema = "cdm_synpuf"
)
disconnect(conn)

## End(Not run)

```

```
renderTranslateQuerySqlToAndromeda
```

Render, translate, and query to local Andromeda

Description

This function renders, and translates SQL, sends it to the server, and returns the results as an ffdf object

Usage

```
renderTranslateQuerySqlToAndromeda(
  connection,
  sql,
  andromeda,
  andromedaTableName,
  errorReportFile = file.path(getwd(), "errorReportSql.txt"),
  snakeCaseToCamelCase = FALSE,
  appendToTable = FALSE,
  oracleTempSchema = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  integerAsNumeric = getOption("databaseConnectorIntegerAsNumeric", default = TRUE),
  integer64AsNumeric = getOption("databaseConnectorInteger64AsNumeric", default = TRUE),
  ...
)
```

Arguments

connection	The connection to the database server created using either connect() or dbConnect() .
sql	The SQL to be send.
andromeda	An open Andromeda object, for example as created using Andromeda::andromeda() .
andromedaTableName	The name of the table in the local Andromeda object where the results of the query will be stored.
errorReportFile	The file where an error report will be written if an error occurs. Defaults to 'errorReportSql.txt' in the current working directory.
snakeCaseToCamelCase	If true, field names are assumed to use snake_case, and are converted to camel-Case.
appendToTable	If FALSE, any existing table in the Andromeda with the same name will be replaced with the new data. If TRUE, data will be appended to an existing table, assuming it has the exact same structure.
oracleTempSchema	DEPRECATED: use tempEmulationSchema instead.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

```

integerAsNumeric
    Logical: should 32-bit integers be converted to numeric (double) values? If
    FALSE 32-bit integers will be represented using R's native Integer class.

integer64AsNumeric
    Logical: should 64-bit integers be converted to numeric (double) values? If
    FALSE 64-bit integers will be represented using bit64::integer64.

...
Parameters that will be used to render the SQL.

```

Details

This function calls the `render` and `translate` functions in the `SqlRender` package before calling [querySqlToAndromeda\(\)](#).

Value

Invisibly returns the andromeda. The Andromeda object will have a table added with the query results.

Examples

```

## Not run:
connectionDetails <- createConnectionDetails(
  dbms = "postgresql",
  server = "localhost",
  user = "root",
  password = "blah",
  schema = "cdm_v4"
)
conn <- connect(connectionDetails)
renderTranslatequerySqlToAndromeda(conn,
  sql = "SELECT * FROM @schema.person",
  schema = "cdm_synpuf",
  andromeda = andromeda,
  andromedaTableName = "foo"
)
disconnect(conn)

andromeda$foo

## End(Not run)

```

`requiresTempEmulation` *Does the DBMS require temp table emulation?*

Description

Does the DBMS require temp table emulation?

Usage

```
requiresTempEmulation(dbms)
```

Arguments

dbms	The type of DBMS running on the server. See connect() or createConnectionDetails() for valid values.
------	--------------------------------------------------------------------------------------------------------------------------------------

Value

TRUE if the DBMS requires temp table emulation, FALSE otherwise.

Examples

```
requiresTempEmulation("postgresql")
requiresTempEmulation("oracle")
```

year	<i>Extract the year from a date</i>
------	-------------------------------------

Description

This function is provided primarily to be used together with `dbplyr` when querying a database. It will also work in `dplyr` against data frames.

Usage

```
year(date)
```

Arguments

date	The date.
------	-----------

Value

The year

Examples

```
year(as.Date("2000-02-01"))
```

Index

Andromeda::andromeda(), 60, 63, 70
assertTempEmulationSchemaSet, 3

computeDataHash, 4
connect, 5
connect(), 4, 7, 11, 12, 20, 21, 40, 48, 50,
 52–54, 56, 58–60, 62, 63, 65, 66, 68,
 70, 72
createConnectionDetails, 9
createConnectionDetails(), 4, 7, 58, 72
createDbiConnectionDetails, 12
createZipFile, 13

data.frame, 25, 26, 30, 47
DatabaseConnectorDriver, 14
DatabaseConnectorDriver(), 21
dateAdd, 14
dateDiff, 15
dateFromParts, 15
day, 16
dbAppendTable, 22–25, 28–30, 36–39, 42–45,
 48
dbAppendTable, DatabaseConnectorConnection, character-method,
 16
dbBind, 18–20, 25, 26, 28, 29, 31–37
dbBind(), 23
dbCanConnect, 28, 29, 36, 37, 46
dbClearResult, 19, 20, 25, 26, 28, 29, 31–37
dbClearResult(), 23, 25, 26, 29, 36, 37,
 43–45
dbClearResult, DatabaseConnectorDbiResult-method,
 18
dbClearResult, DatabaseConnectorJdbcResult-method,
 18
dbColumnInfo, 18, 19, 25, 26, 28, 29, 31–37
dbColumnInfo(), 38
dbColumnInfo, DatabaseConnectorDbiResult-method,
 19
dbColumnInfo, DatabaseConnectorJdbcResult-method,
 20
dbConnect, 28, 29, 36, 37, 46
dbConnect(), 4, 7, 11, 17, 22–24, 29, 38–45,
 47, 48, 50, 52–54, 56, 59, 60, 62, 63,
 65, 66, 68, 70

dbConnect, DatabaseConnectorDriver-method,
 20
dbCreateTable, 18, 23–25, 28–30, 36–39,
 42–45, 48
dbCreateTable(), 16
dbCreateTable, DatabaseConnectorConnection-method,
 21
dbDataType, 18, 22–25, 28–30, 36–39, 42–46,
 48
dbDataType(), 22
dbDisconnect, 18, 22, 24, 25, 28–30, 36–39,
 42–45, 48
dbDisconnect(), 36, 37
dbDisconnect, DatabaseConnectorConnection-method,
 23
dbDriver, 28, 29, 36, 37
dbExecute, 18, 22, 23, 25, 28–30, 36–39,
 42–45, 48
dbExecute(), 16, 21, 27, 29, 30, 44, 45
dbExecute, DatabaseConnectorConnection, character-method,
 23
dbExistsTable, 18, 22–24, 28–30, 36–39,
 42–45, 48
dbExistsTable, DatabaseConnectorConnection, character-method,
 24
dbFetch, 18–20, 28, 29, 31–37
dbFetch(), 19, 20, 29–33, 35, 43, 44
dbFetch, DatabaseConnectorDbiResult-method,
 25
dbFetch, DatabaseConnectorJdbcResult-method,
 26
dbGetException, 18, 22–25, 28–30, 36–39,
 42–45, 48
dbGetInfo, 18–20, 22–26, 30–39, 42–46, 48
dbGetInfo, DatabaseConnectorConnection-method,
 27
dbGetInfo, DatabaseConnectorDriver-method,
 28
dbGetQuery, 18, 22–25, 28, 29, 36–39, 42–45,
 48
dbGetQuery(), 24, 41, 43–45
dbGetQuery, DatabaseConnectorConnection, character-method,
 29

dbGetRowCount, 18–20, 25, 26, 28, 29, 32–37
 dbGetRowCount(), 27, 29
 dbGetRowCount,DatabaseConnectorDbiResult-method dbQuoteIdentifier, 18–20, 25, 26, 28, 29,
 30
 dbGetRowCount,DatabaseConnectorJdbcResult-method dbQuoteIdentifier(), 17, 22, 24, 38, 41, 42,
 31
 dbGetRowsAffected, 18–20, 25, 26, 28, 29,
 31, 33–37
 dbGetRowsAffected(), 23, 27, 29, 45
 dbGetRowsAffected,DatabaseConnectorDbiResult-method, 43–45, 48
 32
 dbGetRowsAffected,DatabaseConnectorJdbcResult-method, 40
 32
 dbGetStatement, 18–20, 25, 26, 28, 29,
 31–33, 35–37
 dbGetStatement(), 27, 29
 dbGetStatement,DatabaseConnectorDbiResult-method, 43
 33
 dbGetStatement,DatabaseConnectorJdbcResult-method dbSendQuery, 18, 22–25, 28–30, 36–39, 42,
 34
 43
 dbHasCompleted, 18–20, 25, 26, 28, 29,
 31–34, 36, 37
 dbHasCompleted(), 27, 29
 dbHasCompleted,DatabaseConnectorDbiResult-method, 34
 35
 dbHasCompleted,DatabaseConnectorJdbcResult-method dbSendQuery(), 18, 24–27, 29–37, 45
 35
 DBIConnection, 17, 22–24, 27–29, 36–39,
 41–45, 47
 DBIDriver, 27, 28, 36, 37
 DBIObject, 27, 28, 36, 37
 DBIResult, 18–20, 25–37, 43–45
 dbIsReadOnly, 18–20, 22–26, 28–39, 42–46,
 48
 dbIsValid, 18–20, 22–26, 28–35, 38, 39,
 42–46, 48
 dbIsValid,DatabaseConnectorDbiConnection-method dbSendStatement, 18, 22–25, 28–30, 36–39,
 42–45, 48
 43
 dbIsValid,DatabaseConnectorJdbcConnection-method dbSendStatement(), 18, 23, 30–37, 43–45
 35
 dbListConnections, 28, 29, 36, 37, 46
 dbListFields, 18, 22–25, 28–30, 36, 37, 39,
 42–45, 48
 dbListFields,DatabaseConnectorConnection, character-method
 38
 dbListObjects, 18, 22–25, 28–30, 36–39,
 42–45, 48
 dbListResults, 18, 22–25, 28–30, 36–39,
 42–45, 48
 dbListTables, 18, 22–25, 28–30, 36–38,
 42–45, 48
 dbListTables,DatabaseConnectorConnection-method dbSendTable, 18, 22–25, 28–30, 36–39, 42,
 44, 45, 48
 47
 49
 dbReadTable, 18, 22–25, 28–30, 36–39,
 47
 dbReadTable,DatabaseConnectorConnection, character-method
 48
 dbRemoveTable, 18, 22–25, 28–30, 36–39, 42,
 44, 45, 48
 49
 dbRemoveTable,DatabaseConnectorConnection, ANY-method,
 42
 dbSendQuery, 18, 22–25, 28–30, 36–39, 42,
 43, 45, 48
 49
 dbSendQuery(), 18, 24–27, 29–37, 45
 dbSendQuery,DatabaseConnectorDbiConnection, character-method
 43
 dbSendQuery,DatabaseConnectorJdbcConnection, character-method
 44
 dbSendStatement, 18, 22–25, 28–30, 36–39,
 42–45, 48
 49
 dbSendStatement(), 18, 23, 30–37, 43–45
 45
 dbSendStatement,DatabaseConnectorConnection, character-method
 46
 dbUnloadDriver,DatabaseConnectorDriver-method,
 46
 dbUnquoteIdentifier, 18–20, 25, 26, 28, 29,
 31–37
 dbWriteTable, 18, 22–25, 28–30, 36–39,
 42–45
 dbWriteTable(), 39, 42
 dbWriteTable,DatabaseConnectorConnection, ANY-method,
 47
 disconnect, 48
 downloadJdbcDrivers, 49
 downloadJdbcDrivers(), 8, 11, 58
 dplyr::tbl(), 55
 dropEmulatedTempTables, 50
 eoMonth, 51
 executeSql, 61
 executeSql(), 65
 existsTable, 52
 extractQueryTimes, 53
 getAvailableJavaHeapSpace, 54
 getTableNames, 54
 id(), 17, 22, 24, 38, 41, 42, 47

inDatabaseSchema, 55
insertTable, 56
isSqlReservedWord, 58

jdbcDrivers, 58

lowLevelExecuteSql, 59
lowLevelQuerySql, 59
lowLevelQuerySqlToAndromeda, 60

month, 61

querySql, 62
querySql(), 59, 67, 69
querySqlToAndromeda, 63
querySqlToAndromeda(), 60, 71

renderTranslateExecuteSql, 64
renderTranslateQueryApplyBatched, 66
renderTranslateQuerySql, 68
renderTranslateQuerySqlToAndromeda, 70
requiresTempEmulation, 71
rownames, 41

SQL(), 17, 22, 24, 38, 41, 42, 47
sqlAppendTable(), 16
sqlAppendTableTemplate(), 16
sqlColumnToRownames(), 41
sqlCreateTable(), 21

year, 72