

Package ‘MissingPlotLSD’

October 12, 2022

Type Package

Title Missing Plot in LSD

Version 0.1.0

Description

A system for Analysis of LSD when there is one missing observation. Methods for this process is described in A.M.Gun,M.K.Gupta,B.Dasgupta(2019,ISBN:81-87567-81-3).

License GPL-3

Encoding UTF-8

RoxygenNote 7.1.2

NeedsCompilation no

Author Debarghya Baul [aut, cre],
Arnab Roy [aut]

Maintainer Debarghya Baul <debarghyabaul@gmail.com>

Repository CRAN

Date/Publication 2022-06-21 09:40:08 UTC

R topics documented:

Missing.LSD	1
Index	3

Missing.LSD	<i>Missing Plot in Latin Square Design(LSD)</i>
-------------	---

Description

This function analyses LSD when there is one missing observation.

Usage

Missing.LSD(data, r, c, t)

Arguments

data	a dataframe which contains values of LSD ,Index No.of row ,Index No.of column,Treatments/Index No.of Treatments in the 1st,2nd,3rd and 4th column respectively. In this dataframe, we will replace the missing value with 0 .
r	the index no. of row containing the missing value.
c	the index no. of column containing the missing value.
t	the index no. of Treatment containing the missing value.

Details

In LSD setup , if there is one missing observation we can use this function to estimate the missing observation along with Sum of Squares for testing the differential effect of the treatments. Here we estimate the missing observation twice by minimizing the SSE of the design.

Value

x.hat : the least square estimate of the missing observation.

SSE.x.hat : Sum of Squares of Error of x.hat.

x.double.hat : the least square estimate of the missing observation under the null hypothesis , H_0 .

SSE.x.double.hat : Sum of Squares of Error of x.double.hat.

F.stat : Observed value of the Test Statistic.

F.crit.value : Critical value of the Test Statistic.

Author(s)

Arnab Roy , Debarghya Baul.

Examples

```
d=OrchardSprays
d[8,1]=0
Missing.LSD(d,8,1,1)
```

Index

Missing.LSD, 1