

Package ‘rdav’

November 1, 2025

Type Package

Title Simple 'WebDAV' Client

Version 0.2.0

Date 2025-10-31

Maintainer Gunther Krauss <guntherkrauss@uni-bonn.de>

Description A simple 'WebDAV' client that provides functions to fetch and send files or folders to servers using the 'WebDAV' protocol (see 'RFC' 4918 <<https://www.rfc-editor.org/rfc/rfc4918>>). Only a subset of the protocol is implemented (e.g. file locks are not yet supported).

License GPL-2

URL <https://github.com/gk-crop/rdav>

BugReports <https://github.com/gk-crop/rdav/issues>

Depends R (>= 4.1.0)

Imports htr2 (>= 1.2.0), xml2

Suggests keyring, knitr, rmarkdown, testthat (>= 3.0.0)

Encoding UTF-8

RoxygenNote 7.3.3

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Gunther Krauss [aut, cre]

Repository CRAN

Date/Publication 2025-11-01 21:30:02 UTC

Contents

ncl_baseurl	2
ncl_shareurl	3
ncl_shareurl_from_publicurl	3
ncl_username_from_url	4
ocs_create_share	5
ocs_delete_share	8
ocs_modify_share	8
ocs_send_mail	9
ocs_shares_extended	10
ocs_share_info	11
rdav	12
wd_connect	13
wd_copy	14
wd_delete	15
wd_dir	15
wd_download	16
wd_isdir	17
wd_mkdir	18
wd_move	18
wd_upload	19
Index	20

ncl_baseurl	<i>Builds the Nextcloud base URL for a nextcloud server from host and user names</i>
-------------	--

Description

Builds the Nextcloud base URL for a nextcloud server from host and user names

Usage

```
ncl_baseurl(hostname, username, path_prefix = "")
```

Arguments

hostname	host name
username	user name
path_prefix	optional path to webdav directory

Value

base url to use with [wd_connect](#)

Examples

```
ncl_baseurl("example.com", "johndoe")
ncl_baseurl("example.com", "johndoe", "sub/dir/")
```

ncl_shareurl	<i>Builds the Nextcloud base URL for a public share from host and user names</i>
--------------	--

Description

Builds the Nextcloud base URL for a public share from host and user names

Usage

```
ncl_shareurl(hostname, username, path_prefix = "")
```

Arguments

hostname	host name
username	user name
path_prefix	ptional path to webdav directory

Value

share url to use with [wd_connect](#)

Examples

```
ncl_shareurl("example.com", "johndoe")
```

ncl_shareurl_from_publicurl	<i>Creates the Nextcloud base URL for a share from a public share url</i>
-----------------------------	---

Description

Creates the Nextcloud base URL for a share from a public share url

Usage

```
ncl_shareurl_from_publicurl(url)
```

Arguments

url link to public share

Value

share url to use with [wd_connect](#)

Examples

```
ncl_shareurl_from_publicurl("https://example.com/s/87d7edad/")
```

ncl_username_from_url *Extracts the user name from a Nextcloud Base URL*

Description

Extracts the user name from a Nextcloud Base URL

Usage

```
ncl_username_from_url(url)
```

Arguments

url base or share url

Value

user name

Examples

```
ncl_username_from_url("https://example.com/remote.php/dav/files/johndoe")
```

ocs_create_share	<i>Creates a share</i>
------------------	------------------------

Description

Creates different share types:

Usage

```
ocs_create_share(  
    req,  
    path,  
    share_type,  
    share_with = NULL,  
    password = NULL,  
    permissions = 1,  
    public_upload = FALSE,  
    expire_date = NULL,  
    label = "",  
    note = "",  
    send_mail = FALSE,  
    attributes = NULL  
)
```

```
ocs_create_share_link(  
    req,  
    path,  
    password = NULL,  
    permissions = 1,  
    public_upload = FALSE,  
    expire_date = NULL,  
    note = "",  
    label = ""  
)
```

```
ocs_create_share_mail(  
    req,  
    path,  
    email,  
    password = NULL,  
    permissions = 1,  
    public_upload = FALSE,  
    expire_date = NULL,  
    note = "",  
    label = "",  
    send_mail = TRUE  
)
```

```

ocs_create_share_user(
    req,
    path,
    user,
    permissions = 1,
    public_upload = FALSE,
    expire_date = NULL,
    note = "",
    label = "",
    send_mail = TRUE
)

ocs_create_share_group(
    req,
    path,
    group,
    permissions = 1,
    public_upload = FALSE,
    expire_date = NULL,
    note = "",
    label = "",
    send_mail = TRUE
)

ocs_create_share_federated(
    req,
    path,
    cloud_id,
    permissions = 1,
    public_upload = FALSE,
    expire_date = NULL,
    note = "",
    label = "",
    send_mail = TRUE
)

```

Arguments

req	WebDAV request as returned by wd_connect
path	folder or file path
share_type	integer 0:user, 1:group, 3:link, 4:e-mail, 6:federated
share_with	depending on share type: user id, group id, e-mail address or federated cloud id (only for ocs_create_share)
password	optional password for link and e-mail shares
permissions	integer (1:read, 2:modify, 4:, 8:, 16:share)
public_upload	TRUE if public upload should be enabled

expire_date	expiration date as string in the format YYYY-MM-DD
label	label for the share
note	note for the share
send_mail	if TRUE the user is notified via e-mail
attributes	optional attributes
email	e-mail address (only for ocs_create_share_mail)
user	id of the user (only for ocs_create_share_user)
group	id of the group (only for ocs_create_share_group)
cloud_id	cloud id (only for ocs_create_share_federated)

Details

- ocs_create_share - generic method that takes share type as argument
- ocs_create_share_user - creates a share for a nextcloud user
- ocs_create_share_group - creates a share for a nextcloud group
- ocs_create_share_link - create a public share link
- ocs_create_share_mail - creates an e-mail share
- ocs_create_share_federated - creates a federated share

Notice: if protecting a public link or e-mail share with a password, make sure that the password meets the services' password policy.

Value

information for the newly created share as data.frame

Examples

```
## Not run:
r <- wd_connect("https://example.com/remote.php/dav/files/johndoe")
ocs_create_share(r, "myfolder/share", 4)
ocs_create_share_link(r, "myfolder/share")
ocs_create_share_mail(r, "myfolder/share", "jack@example.com")
ocs_create_share_user(r, "myfolder/share", "jackdoe")

## End(Not run)
```

ocs_delete_share	<i>Deletes a share</i>
------------------	------------------------

Description

Deletes a share

Usage

```
ocs_delete_share(req, id)
```

Arguments

req	WebDAV request as returned by wd_connect
id	share id

Value

invisible boolean TRUE on success and FALSE on failure

Examples

```
## Not run:  
r <- wd_connect("https://example.com/remote.php/dav/files/johndoe")  
ocs_delete_share(r, 12342)  
  
## End(Not run)
```

ocs_modify_share	<i>Modifies properties of a share</i>
------------------	---------------------------------------

Description

If a parameter omitted or is NULL, then the corresponding property is not modified.

Usage

```
ocs_modify_share(  
  req,  
  id,  
  password = NULL,  
  permissions = NULL,  
  public_upload = NULL,  
  expire_date = NULL,  
  label = NULL,
```



```
    note = NULL,  
    send_mail = NULL,  
    attributes = NULL  
  )
```

Arguments

req	WebDAV request as returned by wd_connect
id	share id
password	optional password for link and e-mail shares
permissions	integer (1:read, 2:modify, 4:, 8:, 16:share)
public_upload	TRUE if public upload should be enabled
expire_date	expiration date as string in the format YYYY-MM-DD
label	label for the share
note	note for the share
send_mail	if TRUE the user is notified via e-mail
attributes	optional attributes

Value

data.frame with the share properties

Examples

```
## Not run:  
r <- wd_connect("https://example.com/remote.php/dav/files/johndoe")  
ocs_modify_share(r, 12345, permissions = 31, expire_date = "2025-11-01")  
  
## End(Not run)
```

ocs_send_mail	<i>Notifies the user of a mail share</i>
---------------	--

Description

Notifies the user of a mail share

Usage

```
ocs_send_mail(req, id, password = NULL)
```

Arguments

req	WebDAV request as returned by wd_connect
id	share id
password	password of the share if it is password protected

Value

invisible TRUE on success or FALSE on failure

Examples

```
## Not run:
r <- wd_connect("https://example.com/remote.php/dav/files/johndoe")

# add a password to a mail share and notify the user
ocs_modify_share(r, 12342, password = "super_secret")
ocs_send_mail(r, 12342, password = "super_secret")

## End(Not run)
```

ocs_shares_extended	<i>Returns information for shares</i>
---------------------	---------------------------------------

Description

ocs_shares_extended returns extended information for shares. ocs_shares returns the shares of a file or folder, ocs_child_shares the shares of the files and subfolders of the given path.

Usage

```
ocs_shares_extended(
  req,
  path = "",
  as_df = TRUE,
  columns = NULL,
  subfiles = TRUE,
  reshares = FALSE
)

ocs_child_shares(
  req,
  path = "",
  as_df = TRUE,
  columns = c("share_type", "item_type", "permissions", "label", "uid_owner",
    "share_with_displayname")
)

ocs_shares(
  req,
  path = "/",
  as_df = TRUE,
  columns = c("share_type", "item_type", "permissions", "label", "uid_owner",
    "share_with_displayname")
)
```

Arguments

req	WebDAV request as returned by wd_connect
path	folder or file path
as_df	if TRUE (default) a data.frame is returned, else a list of IDs
columns	column names that should be included into the result (default NULL includes all)
subfiles	list shares of subfolders
reshares	include shares from others

Value

data.frame or named vector of IDs

Examples

```
## Not run:
r <- wd_connect("https://example.com/remote.php/dav/files/johndoe")
ocs_shares_extended(r, "myfolder/shares")
ocs_shares(r, "myfolder/shares")
ocs_child_shares(r, "myfolder")

## End(Not run)
```

ocs_share_info	<i>Get infor for a specific share</i>
----------------	---------------------------------------

Description

Get infor for a specific share

Usage

```
ocs_share_info(req, id, columns = NULL)
```

Arguments

req	WebDAV request as returned by wd_connect
id	share id
columns	column names that should be included into the result (default NULL includes all)

Value

one row data.frame with share properties

Examples

```
## Not run:
r <- wd_connect("https://example.com/remote.php/dav/files/johndoe")
ocs_share_info(r, 158742)

## End(Not run)
```

rdav

rdav: Interchange Files With 'WebDAV' Servers

Description

Provides functions to interchange files with WebDAV servers

Details

- download a file or a directory (recursively) from a WebDAV server
- upload a file or a directory (recursively) to a WebDAV server
- copy, move, delete files or directories on a WebDAV server
- list directories on the WebDAV server

Notice: when uploading or downloading files, they are overwritten without any warnings.

Author(s)

Gunther Krauss

See Also

Useful links:

- <https://github.com/gk-crop/rdav>
- Report bugs at <https://github.com/gk-crop/rdav/issues>

Examples

```
## Not run:
# establish a connection, you will be asked for a password
r <- wd_connect("https://example.com/remote.php/webdav/", "exampleuser")

# show files / directories in main directory
wd_dir(r)

# lists 'subdir', returns a dataframe
wd_dir(r, "subdir", as_df = TRUE)

# create directory 'mydirectory' on the server
wd_mkdir(r, "mydirectory")
```

```
# upload the local file testfile.R to the subdirectory 'mydirectory'
wd_upload(r, "testfile.R", "mydirectory/testfile.R")

# download content of 'mydirectory' from the server and
# store it in 'd:/data/fromserver' on your computer
wd_download(r, "mydirectory", "d:/data/fromserver")

## End(Not run)
```

wd_connect	<i>Establishes a connection to a WebDAV server</i>
------------	--

Description

Creates and authenticate a request handle to the WebDAV server

Usage

```
wd_connect(url, username = ncl_username_from_url(url), password = NULL)
```

Arguments

url	url of the WebDAV directory
username	username - if not given, it will be derived from the url
password	password - if not given, you will be asked for it

Details

Notice: it's not recommended to write the password as plain text. Either omit the parameter (then you will be asked to enter a password interactively) or use for example the system credential store via keyring package.

Value

a http2 request to the WebDAV server location

Examples

```
## Not run:
# establish a connection, you will be asked for a password

r <- wd_connect("https://example.com/remote.php/webdav/", "exampleuser")

# establish a connection, use keyring package to retrieve the password
```

```
keyring::key_set("mydav", "exampleuser") # call only once

r <- wd_connect("https://example.com/remote.php/webdav/",
               "exampleuser",
               keyring::key_get("mydav", "exampleuser"))

## End(Not run)
```

wd_copy*Copies a file or directory on the WebDAV server*

Description

Copies a file or directory on the WebDAV server

Usage

```
wd_copy(req, source, target, overwrite = TRUE)
```

Arguments

req	request handle obtained from wd_connect
source	path of the source on the server
target	path of the target on the server
overwrite	overwrites files when TRUE (default)

Value

TRUE on success, FALSE on failure (invisibly)

Examples

```
## Not run:

wd_copy(r, "testfile.R", "testfile_old.R")

## End(Not run)
```

wd_delete	<i>Deletes a file or directory (collection) on WebDAV server</i>
-----------	--

Description

Deletes a file or directory (collection) on WebDAV server

Usage

```
wd_delete(req, file)
```

Arguments

req	request handle obtained from wd_connect
file	path to file or directory to delete on the server

Value

TRUE on success, FALSE on failure (invisibly)

Examples

```
## Not run:  
  
wd_delete(r, "testfile.R")  
  
## End(Not run)
```

wd_dir	<i>Lists the content of a WebDAV directory</i>
--------	--

Description

Lists the content of a WebDAV directory

Usage

```
wd_dir(req, directory = "", full_names = FALSE, as_df = FALSE)
```

Arguments

req	request handle obtained from wd_connect
directory	directory path
full_names	if TRUE, the directory path is prepended to the file names to give a relative file path (relevant only if as_df is FALSE)
as_df	if TRUE outputs a data.frame with file information

Value

a vector of filenames or a dataframe (when `as_df` is TRUE) with detailed file information (filename, path, isdir, size, lastmodified)

Examples

```
## Not run:

# lists names of files and directories in the main directory
wd_dir(r)

# lists names of files and directories in the subdirectory "mydirectory"
wd_dir(r, "mydirectory")

# lists names of files and directories with the relative path
wd_dir(r, "mydirectory", full_names=TRUE)

# returns a data.frame with the columns filename, size and isdir (whether
# it's a directory or file
wd_dir(r, "mydirectory", as_df=TRUE)

## End(Not run)
```

wd_download

Fetches a file or directory (recursively) from the WebDAV server

Description

Directories are downloaded recursively. If the source is a file and the target a directory, then the file is downloaded to the target directory. If the target is omitted, then the file or directory name ([basename](#)) will be used.

Usage

```
wd_download(req, source, target = "")
```

Arguments

req	request handle obtained from wd_connect
source	path to source file or directory on server
target	path to local target file or directory, if omitted the file or directory name will be used, if source is a file and target a directory then the file will be put into the target directory

Value

vector of downloaded files (invisibly)

Examples

```
## Not run:

wd_download(r, "weatherfiles", "d:/data/weather")
wd_download(r, "test/xyz.txt", "d:/data/abc.txt")

## End(Not run)
```

wd_isdir	<i>Checks if the resource on WebDAV is a directory</i>
----------	--

Description

Checks if the resource on WebDAV is a directory

Usage

```
wd_isdir(req, directory, silent = FALSE)
```

Arguments

req	request handle obtained from wd_connect
directory	path to directory
silent	if FALSE a warning is given if the directory does not exists

Value

TRUE if it is a directory, FALSE else

Examples

```
## Not run:

wd_isdir(r, "testfile.R") # FALSE
wd_isdir(r, "mydirectory") # TRUE

## End(Not run)
```

wd_mkdir	<i>Creates a directory (collection) on WebDAV server</i>
----------	--

Description

When creating a subdirectory, all parent directories have to exist on the server.

Usage

```
wd_mkdir(req, directory)
```

Arguments

req	request handle obtained from wd_connect
directory	directory path on server

Value

TRUE on success, FALSE on failure (invisibly)

Examples

```
## Not run:  
  
# creates 'newdir' inside the subdirectory 'existing/directory'  
wd_mkdir(r, "existing/directory/newdir")  
  
## End(Not run)
```

wd_move	<i>Moves a file or directory on the server</i>
---------	--

Description

Moves a file or directory on the server

Usage

```
wd_move(req, source, target, overwrite = TRUE)
```

Arguments

req	request handle obtained from wd_connect
source	path of the source on the server
target	path of the target on the server
overwrite	overwrites files when TRUE (default)

Value

TRUE on success, FALSE on failure (invisibly)

Examples

```
## Not run:

wd_move(r, "testfile.R", "testfile_old.R")

## End(Not run)
```

wd_upload

Uploads a file or directory to WebDAV

Description

Directories are uploaded recursively. If the source is a file and the target a directory, then the file is uploaded into the directory. If the target is omitted, then the file or directory name ([basename](#)) will be used.

Usage

```
wd_upload(req, source, target = "")
```

Arguments

req	request handle obtained from wd_connect
source	path to local file or directory
target	path to remote file or directory, if omitted the file or directory name will be used, if source is a file and target a directory then the file will be put into the target directory

Value

vector of uploaded files (invisibly)

Examples

```
## Not run:

wd_upload(r, "d:/data/weather", "weatherfiles")
wd_upload(r, "d:/data/abc.txt", "test/xyz.txt")
wd_upload(r, "d:/data/abc.txt", "test") # uploaded file will be test/abc.txt

## End(Not run)
```

Index

basename, [16](#), [19](#)

ncl_baseurl, [2](#)

ncl_shareurl, [3](#)

ncl_shareurl_from_publicurl, [3](#)

ncl_username_from_url, [4](#)

ocs_child_shares (ocs_shares_extended),
[10](#)

ocs_create_share, [5](#)

ocs_create_share_federated
(ocs_create_share), [5](#)

ocs_create_share_group
(ocs_create_share), [5](#)

ocs_create_share_link
(ocs_create_share), [5](#)

ocs_create_share_mail
(ocs_create_share), [5](#)

ocs_create_share_user
(ocs_create_share), [5](#)

ocs_delete_share, [8](#)

ocs_modify_share, [8](#)

ocs_send_mail, [9](#)

ocs_share_info, [11](#)

ocs_shares (ocs_shares_extended), [10](#)

ocs_shares_extended, [10](#)

rdav, [12](#)

rdav-package (rdav), [12](#)

wd_connect, [2–4](#), [6](#), [8](#), [9](#), [11](#), [13](#), [14–19](#)

wd_copy, [14](#)

wd_delete, [15](#)

wd_dir, [15](#)

wd_download, [16](#)

wd_isdir, [17](#)

wd_mkdir, [18](#)

wd_move, [18](#)

wd_upload, [19](#)