TEN 47.

D

ANNEX I

CCITT DRAFT RECOMMENDATION ON THE NUMBERING PLAN FOR PUBLIC DATA NETWORKS

· Draft recommendation X

International numbering plan for public data networks

The purpose of this International Numbering Plan is to facilitate the introduction of public data networks and provide for their interworking on a worldwide basis.

Design considerations

1.

1.1

The design considerations that form the basis of this Plan are as follows :

that there could be a number of public data networks in a country ";

1.2 that where a number of public data networks are to be established in a country, it should not be mandatory to integrate the numbering plans of the various networks;

1.3 that the International Numbering Plan should permit the identification of a called country as well as a specific public data network in that country";

1.4 that the number of digits comprising the code used to identify a country* and a specific public data network in that country*should be the same for all countries*;

1.5 that a national data number assigned to a data terminal should be unique within a particular national network. This national data number should form part of the international data number which should also be unique on a worldwide basis;

1.6 that the number of digits to be used in an international data number should be governed by national and international requirements but a reasonable limit on the overall number of digits should be imposed;

1.7 that the Numbering Plan should make provision for the interworking of public data networks with data terminals on public telephone and telex* "networks;

1.8 that the international Numbering Plan should provide for substantial spare capacity to accommodate future requirements:

1.9 that the Numbering Plan should not preclude the poscibility of a single national network providing an integrated telecommunications system for services of all kinds;

10 that where multiple RPOA facilities exist providing service to the same country *, rovision for the selection of a specific RPOA facility should be allowed for in the Facility Request part of the Selection Signals.

.2. Characteristics and application of the Numbering Plan

2.1 Number system

2.1.1 The 10 digit numeric character set 0 - 9 should be used for numbers (or addresses) assigned to data terminals on public data networks. This principle should apply to both national and international data numbers.

2.1.2 Use of the above number system will make it possible for data terminals on public data networks to interwork with data terminals on public telephone and telex networks.

* Country or geographical area

The term "telex" employed in this Recommendation, includes TWX networks.

Data network identification codes

2.2.1 A data network identification code (DNIC) should be assigned to each public data network or, possibly where all networks are contained within an integrated numbering scheme, to each specific service.

2.2.2 All data network identification codes (DNIC) should consist of 4 digits. The first 3 digits should always identify a country and could be regarded as a data country code (DCC). The fourth, or network digit, should identify a specific data network or service in the country as indicated in 2.2.1.

2.2.3 Each country' should be assigned at least one 3 digit data country' code (DCC). The data country' code (DCC) in conjunction with the fourth digit can identify up to 10 public data networks. The format for data network identification codes (DNIC) should be as indicated below:



Teu trans anne a se seultrees :

X - denotes any digit from 0 through 9

Z - denotes any digit from 2 through 7 as indicated in 2.2.4

2.2.4

In the system of data network identification codes, the first digit of such codes should be in accordance with the following list.

1 - } Reserved
2 3 4 5 6 7 -

8 - For interworking with telex networks

- For interworking with telephone networks

Note 1 : The allocation of codes for non-zoned services, such as : Marine Satellite Services, is for further study. (Refer to Joint Working Party SMM). The following points could be considered :

- select a data country' code (DCC) in each zone to indicate the location, or

- use an escape DNIC such as : 11XX.

Note 2 : Details on the numbering plan aspects of interworking between public data networks and public telephone and telex networks will be given in another Recommendation.

2.2.5 The system of data network identification codes (DNIC) indicated in 2.2.3 and 2.2.4 will provide for 600 data country" code (DCC) and a theoretical maximum of 6 000 DNIC.

2.2.6 Should a country' have more than 10 public data networks, an additional data country' code(s)(DCC) would be assigned to it.

....ountry or geographical area

2.2.7 A list of data country codes (DCC) to be used in the development of data network identification codes (DNIC) is given in Appendix B to this Recommendation. This list was prepared in accordance with the requirement that the first digit of a DNIC, which is also the first digit of the embedded data country code (DCC) should be restricted to the digits 2-7 inclusive (ref:2.2.4). As first digits of data country codes (DCC) the digits 2-7 are arranged to represent world zones.

2.2.8 The assignment of data country* codes (DCC) is to be administered by the CCITT. The assignment of network digits will be made nationally and the CCITT Secretariat notified.

The Member countries of the Union not mentioned in this list who wish to take part in the international data service or those members who require an additional data country* code(s) (DCC) should ask the Director of the CCITT for the assignment of an available three-digit data country* code(s) (DCC). In their request, they may indicate the available three-digit code(s) preferred.

Assignments by the Director of the CCITT of data country* codes (DCC) as well as assignments by countries* of network digits will be published in the Operational Bulletin of the ITU.

2.2.9 Examples indicating how data network identification codes (DNIC) could be developed, are given in Appendix A to this Hecommendation.

2.3 International data number

2.3.1 A data terminal on a public data network when called from another country^{*} should be addressed by its international data number. The international data number should consist of the data network identification code (DNIC) of the called public data network, followed by the network terminal number (NTN) of the called data terminal, or, for example, where an integrated numbering scheme exists within a country^{*}, the data country^{*} code (DCC) followed by the national number (NN) of the called terminal, i.e:

INTERNATIONAL DATA NUMBER = DNIC + NTN, or, DCC + NN

2.3.2 The network terminal number (NTN) should consist of the full address that is used when calling the data terminal from within its serving public data network. Alternatively, the national number (NN) should consist of the full address used when calling the data terminal from another terminal within the national integrated numbering scheme. These numbers should consist of all the digits necessary to uniquely identify the data terminal within the serving network and should not include any prefix (or access code) that might be employed for such calling.

2.4 <u>Maximum number of digits</u>

2.4.1 International data numbers could be of different lenghts but should not consist of more than 14 digits. With the data network identification code (DNIC) fixed at 4 digits and the data country code (DCC) fixed at 3 digits, it would, therefore, be possible to have a network terminal number (NTN) of 10 digits maximum, or, a national number (NN) of 11 digits maximum.

NOTE: The limit of 14 digits specified above applies exclusively to the address information. Adequate register capacity should be made available at data switching exchanges to accomodate the above address digits as well as any additional digits that might be introduced for signalling, or other purposes.

Country or geographical area

International prefix

2.5.1 For outgoing international calls from a public data network, an international prefix (or access code) would generally be required to access appropriate facilities for international interworking. The composition of this prefix is a national matter as the prefix does not form part of the international data number. However, the possible need to accommodate such a prefix with regard to digit register capacity in the calling network should be noted.

sevis at (0100) soboo holtsollina

A-Mast of data country" codes

2.6 Number analysis - international calls between public data networks

2.6.1 In the case of international calls between public data networks, provision should be made at originating countries to interpret the first three digits of the international data number. These digits constitute the data country code (DCC) component of the data network indentification code (DNIC) and identify the terminal country. This information is required at the originating country for routing purposes.

2.6.2 At originating countries, it might also be necessary to interpret the fourth, or network digit, of a DNIC. Such interpretation would provide the identity of a specific network in a country where several public data networks are in service. This information .ght be required for billing purposes or for the selection of specific routes to called networks.

Note: With regard to RPOA selection, see paragraph 1.10.

2.6.3 Countries* receiving international calls for public data networks should receive the complete international data number including the data network identification code (DNIC). However, where a country* of destination indicates that it does not wish to receive the data country* code (DCC) component of the DNIC, arrangements should be made to suppress the DCC.

2.6.4 For destination countries with more than ten public data networks, interpretation of the first three digits of the DNIC (i.e., the data country code (DCC)) would identify the group of networks within which the called network is included. Interpretation of the fourth or network digit of the DNIC would identify the called network in that group. Interpretation of the first three digits would also make it possible to verify that an incoming call has in fact reached the correct country.

2.6.6 At transit countries, the complete international data number including the data network identification code (DNIC) must always be received. Interpretation of the first three digits would identify the called country. Interpretation of the fourth or network digit would non-tify a specific data network or a service in the called country. Interpretation of the fourth digit might be required for billing purposes or for route selection beyond the transit country.

2.6.7 Where a data call is to be routed beyond a transit country through a second transit country, the complete international data number, including the data network identification code (DNIC) should always be sent to the second transit country. Where the data call is to be routed by a transit country to the country of destination, the arrangements indicated in section 2.6.3 should apply.

ents Inslightsh

2.7 Directories and letterheads

Country or geographical area

2.7.1 Directories for public data networks should include information on the procedures to be followed for making international data calls. A diagram, such as that of Figure 1, could assist the customer in these procedures.

2.7.2 With regard to the prefix (or access code) shown in Figure 1, it should be noted that the same prefix (designated P) could be used for all three types of calls. The choice of prefix is, however, a national matter.

2.7.3 With regard to RPOA Selection (see Section 1.10) it should be noted that a RPOA facility request designator would be used only in international data calls. Provision of this facility as well as the designation of the RPOA facility selection designator is a national matter in the originating country."

2.7.4 With regard to the publication of international data numbers on letterheads or other written material, it is recommended that the network terminal number (NTN) or_ national number (NN) should be easily distinguished within the international number, i.e. that there be a space between the 4 digit DNIC and the network terminal number (NTN) or, between the 3 digit data country code (DCC) and the national number (NN) where the fourth digit of the DNIC is included in the national number (NN).

International Calling Format

(Fig. 1A - International call between data terminals on public data networks.
 (a) - Called number is not part of a national integrated numbering scheme.
 (b) - Called number is part of a national integrated numbering scheme.

Fig. 18 - International call from a data terminal on a public data network to a data terminal on a public telephone network.

Fig. 1C - International call from a data terminal on a public data network to a data terminal on a telex network.



Legend

augunu.

P - International Prefix

DNIC - Data Network Identification Code

DCC - Data Country Code

TCC - Telephone Country Code

TDC - Telex Destination Code

APPENDIX A

Development of Data Network Identification Codes (DNIC)

Examples

Example 1

In this example, it is assumed for illustrative purposes only, that the Netherlands has established its first public data network. To develop the data network identification code (DNIC) for this network, it would be necessary for the Netherlands to assign to it a network digit to follow the listed data country^{*} code (DCC) 204 (see Annex 2). Assuming that the Netherlands selected the digit 0 as the network digit, the data network identification code (DNIC) for this initial network would be 2040.

Example 2

In this example, it is assumed for illustrative purposes only, that five public data networks have been established in Canada. To develop the data network identification codes for these networks, it would be necessary for Canada to assign to each of these networks a network digit to follow the listed data country code (DCC) 302 (See Annex 2). Assuming that Canada assigned the network digits 0-4 to the five networks, the resulting data network identification codes (DNIC) would be 3020, 3021, 3022, 3023 and 3024.

Example 3

In this example, it is assumed for illustrative purposes only, that eight public data networks have been established in the United States of America. It is also assumed that network digits 0-7 would be assigned by the United States of America to follow the listed data Country' code (DCC) 310 (see Annex 2). The data network identification codes (DNIC) thus formed for these eight networks would be 3100, 3101, 3102, 3103, 3104, 3105, 3106, and 3107.

If some time later, four additional public data networks were to be introduced in the United States of America, two of the four new networks could be assigned network digits 8 and 9 in association with data country" code (DCC) 310, to produce the data network identification codes (DNIC) 3108 and 3109.

For the remaining two public data networks, the United States of America would have to ask the CCITT for an additional data country[®] code (DCC). A request for a code next in sequence, i.e. 311, could be made if this code appeared to be spare. If code 311 could be made available it would be assigned to the United States of America. If it was not available, a spare code in the "300" series of data country[®] codes (DCC) would be assigned. Assuming data country[®]code (DCC) 311 was available and issued to the United States of America, the two remaining public data networks could be assigned network digits 0 and 1 in association with data country[®] code (DCC) 311, to produce the data network identification codes (DNIC) 3110 and 3111.

The data network identification codes (DNIC) for the 12 public data networks would then be 3100, 3101, 3102, 3103, 3104, 3105, 3106, 3107, 3108, 3109, 3110 3111.

Example 4

In this example it is assumed, for illustrative purposes only, that a public data network is to be established in each of two Caribbean islands that are part of the group of islands known as the French Antilles. The islands concerned are Guadeloupe and Martinique. To develop the data network identification codes (DNIC) for these public data etworks, it is assumed that the French Administration would assign network digit 0 to the network in Guadeloupe and network digit 1 to the network in Martinique and associate these network digits with the listed data country' code (DCC) 340 for the French Antilles (see Annex 2). The data network identification codes (DNIC) thus formed would be 3400 for Guadeloupe and 3401 for Martinique.

This example indicates that the system of data network identification codes (DNIC) is appropriate for application to groups of islands or regions of a country since one data country code (DCC) could provide for up to ten public data networks dispersed over several islands or regions. At the same time such island or regional networks would be distinguishable from each other.

evelop to it a servoy digit to follow the listed data country! code (100) 20% (see

public data mervarks have been established in Gamada. To develop the data network Meruiffication codes for these cetworks,it would be measurery for Caneda to assign to each of these networks a metwork digit to fellow the listed data country" code (1000) 302 (See Annew 2). Assuning that Gandda assigned the metwork digits O.A to the five setumine, the resulting data metwork identification codes (1000) 3022, 3023 and 3024.

In this example, it is availed for illustrative purposes only, that sight public data networks have been established in the United States of America. It is also assumed that network digits 0-7 would be assigned by the United States of America to failow the iterest data downtry, seds (2001) 210 (see Annex 21. The data asteury identification codes (DSED) thus formed for these sight networks would be 3100, 3102, 3103, 3105, 3105, 5105, and 5107.

If sime the later, four estimation public data networks very to be introduced in the Daited States of Josefins, two of the four day networks could be seeigned network digits & and 5 is accordation with data senatry" code (200) 310, to produce the data network identification secon (DDTO) 3100 and 3107.

New the rescaledon two public data metworks, the United States of Acetica would have to ask the GENTY for an additional data country? onde (CGC). A request for a code meric is sequence; i.e. 31, could be made if this code appeared to be sparsed. If ands 311 could be made available it would be semigned to the Onited States of America, if it was not available, a spare your to the "300" series of data "theiry? sedes (SGO) would be semigned. Annuming data country'out (GGO) 311 was aceticable and termed to the United States of America, the two remaining public data metworks shuld be semigned actuary digits 0 and 1 to association with data country" code (EGG) 311, to produce the data setwork identification some (DNTO) 3110 and 3111.

The data network identification codes (DNHC) for the 12 public data networks weble, Shen he \$100, \$101, 5102, 5103, 5103, 5105, 5105, 5106, 5109, 5100

In this example it is estund, for illustrative purposes only, that a public data network is to be established in such of two Carlibness (simils that are gait of the group of datasets shown as the French Amilian. The islands concerved are Contribute and Martinique.

Mountry of generalities.

9

.

APPENDIX

LIST OF DATA COUNTRY OR GEOGRAPHICAL AREA CODES

NOTE: The countries or geographical areas shown in this Annex include those that already have code assignments in the case of other public telecommunications networks.

ZONE 2		
Code	Country or Geographical Area	
		Protoch Antilley
202	Greece	
204	Netherlands (Kingdom of the)	Aughtenk
206	Belgium	
208	France	sintin I again this roll
212	Monaco	
214	Spain	
216	Hungarian People's Republic	
218	German Democratic Republic	177.2X 2B
220	Yugoslavia (Socialist Federal	Republic of)
222	Italy	St. Vincest.
226	Romania (Socialist Republic of) and the set of the set of the set
228	Switzerland (Confederation of)	
230	Czechoslovak Socialist Republi	
232	Austria -	
234	United Kingdom of Great Britai	n and Northern Ireland
238	Denmark	[10 eridungelij staal
240	- Sweden	Trinidad and Tobero
242	Norway	
250	Union of Soviet Socialist Repu	blics
260	Poland (People's Republic of)	
262	Germany (Federal Republic of)	
266	Gibraltar	
268	Portugal	
270	Luxembourg	•
272	Ireland	
274	Iceland	
276	Albania (People's Republic of)	
278	Malta (Republic of)	
280	Cyprus (Republic of)	
282	Finland	

Bulgaria (People's Republic of) 284 286 Turkey

Zone 2, Spare Codes: 68

			Lann
			AIDIEX
		E man	Page
ZONE 3		Ap	pendix
20146 3		APPENDIX	
Code	Countries on Conservation 2 Annual		
code	Country or Geographical Area		1 2
302	Counda		
308	Canada		
310	St Pierre and Miquelon United States of America		÷.
330	Puerto Rico		
332	Virgin Islands (USA)		
334	Mexico		
338	Tamaian		
340	French Antilles		
342	Barbados		
344	A . I . DOBUTU		
346 346	Antigua Cayman Islands		
348	Pritich Wir in Transf		
	Banmuda		
350	Group 2		
352		· 8.12	
154			
56			
58 60	St Lucia		
62	St Vincent		
64	Netherlands Antilles		
	Bahamas (Commonwealth of the)		
66	Dominica		
68	Cuba - Alectonik		
70	Dominican Republic		1
72	Haiti (Republic of)		
74	Trinidad and Tobago		
76	Turks and Caicos Islands		
	Union of Soviet Socielist Repúblics		
	Germany (Federal Republic of)		
one 3,	Spare Codes: 74		
	. Isynthol		
	Puroquexury		
1			
ONE 4	hanlesT		
ada	Albanta (Poogle's Sepublic of)		
ode	Country or Geographical Area		
	Gypeus (Sepublic of)		
04	India (Republic of)		
10 12	Pakistan (Islamic Republic of)		
	Afghanistan (Republic of)		
13	Sri Lanka (Ceylon) (Republic of)		
4	Burma (Socialist Republic of the Union of)		
15	Lebanon		
16	Jordan (Hashemite Kingdom of) 83 method water		
7	Syrian Arab Republic	1.1	
18	Iraq (Republic of)		
19	Kuwaite (State of)		
20	Saudi Arabia (Kingdom of)		
21	Hemen (Arab Republic		
22	Oman (Sultanate of)		
23	Yemen (People's Domogratic Republic of)		

(

. 8

C

0:

ADDIEX I Page 11. Appendix B

. .

613

. .

(to plicage) and lot

Equatorial Cultant (Bas

Gainen Republic

ZONE 4 (Cont)

	Code	Country or Geographical Area
	Disease:	Coultry or Cookraphioni. Areas *
	424	United Arab Emirates
	425	Israel (State of)
	426	Bahrain (State of)
	427	Qatar (State of)
	428	Mongolian People's Republic
	429	Nepal mbmsfal dool
	430	United Arab Emirates (Abu Dhabi)
	431	United Arab Emirates (Dubai)
5	432	Iran
	440	Japan
	450	Korea (Republic of)
	452	Viet Nam (Socialist Republic of)
	454	Hong Kong
	455	Macao
	456	Democratic Kampuchea
	457	Lao People's Democratic Republic
	460	China (People's Republic of)
	470	Bangladesh (People's Republic of)
	472	Maldives (Republic of)
		*UAE: (Ajman, Fujairah, Ras Al Khaimah, Sharjah,
		the Al Oinsin)

Umm Al Qiwain)

Zone 4, Spare Codes: 67

ZONE 5

Code	Country or Geographical Area	
502	Malaysia	
505	Australia	
510	Indonesia (Republic of)	
515	Phillipines (Republic of)	
520	Thailand	
525	Singapore (Republic of)	
528	Brunei	
530	New Zealand	
535	Guam	
536	Nauru (Republic of)	
537	Papua New Guinea	
539	Tonga (Kingdom of)	
540	Solomon Islands	
541	New Hebrides	
542	Fiji	
543	Wallis and Futuna Islands	
10000		

ANNEX I Page 12 Appendix B

. .

0.8

ZOME 5 (Cont)

Country or Geographical Area Code 544 Americal Samoa Gilbert & Ellice Islands 545 New Caledonia and Dependencies 546 547 French Polynesia 548 Cook Islands 549 Western Samoa

Zone 5, Spare Codes: 78

ZONE 6

Code Country or Geographical Area 602 Egypt (Arab Republic of) Algeria (Algerian Democratic and Popular Republic) 603 604 Morocco (Kingdom of) 605 Tunisia Socialist People's Libyan Arab Jamahiriya 606 607 Cambia (Republic of) 608 Senegal (Republic of) Mauritania (Islamic Republic of) 609 610 Mali (Republic of) 611 Guinea (Republic of) 612 Ivory Coast (Republic of the) 613 Upper Volta (Republic of) 614 Niger (Republic of the) 615 Togolese Republic 616 Benin (People's Republic of) 617 Mauritius 618 Liberia (Republic of) 619 Sierra Leone 620 Ghana 621 Nigeria (Federal Republic of) 622 Chad (Republic of the) Central African Empire Cameroon (United Republic of) 623 624 625 Sao Thome and Principe (Democratic Republic of) Equatorial Guinea (Republic of) 626 Equatorial Guinea (Republic of) 627 (the select of the select 628 Gabon Republic 629 Congo (People's Republic of the) 630 Zaire (Republic of) 631 Angola (People's Republic of) 632 Guinea-Bissau (Republic of) 633 Seychelles 634 Sudan (Democratic Republic of the) 635 Rwanda (Republic of)

(hedd) anterial dork bed ed)

ANNEX I Page 13. Appendix B

ZONE 6 (Cont)

. EC

Ď

5.

1

Code	Country or Geographical Area
636	Ethiopia
637	Somali Democratic Republic
638	Republic of Djibouti
639	Kenya (Republic of)
640	Tanzania (United Republic of) (Mainland)
641	Uganda (Republic of)
642	Burundi (Republic of)
643	Mozambique (People's Republic of)
645	Zambia (Republic of)
646	Madagascar (Democratic Republic of)
647	Reunion (French Department of)
648	Southern Rhodesia
649	Namibia
650	Malawi
651	Lesotho (Kingdom of)
652	Botswana (Republic of)
653	Swaziland (Kingdom of)
654	Comoros (State of the)
655	South Africa (Republic of)

Zone 6, Spare Codes: 47

ZONE 7

Code	Country or Geographical Area	
702	Belize	
704	Guatemala(Republic of)	
706	El Salvador (Republic of)	
708	- Honduras (Republic of)	
710	Nicaragua	
712	Costa Rica	
714	Panama (Republic of)	
716	Peru	
722	Argentine Republic	
724	Brazil (Federative Republic of	.)
730	Chile	'
732	Columbia (Republic of)	
734	Venezuela(Republic of)	
736	Bolivia (Republic of)	
738	Guyana	
740	Ecuador	
742	Guiana (French Department of)	
744	Paraguay (Republic of)	
746	Surinam (Republic of)	
748	Uruguay (Oriental Republic of)	